



Right to Know Hazardous Substance Fact Sheet

Common Name: **ALUMINUM NITRATE**

Synonyms: Aluminum Trinitrate

Chemical Name: Nitric Acid, Aluminum Salt

Date: January 2001 Revision: May 2010

CAS Number: 13473-90-0

RTK Substance Number: 0061

DOT Number: UN 1438

Description and Use

Aluminum Nitrate is an odorless, colorless to white solid. It is used in tanning leather and as an antiperspirant, corrosion inhibitor and nitrating agent.

Reasons for Citation

- ▶ **Aluminum Nitrate** is on the Right to Know Hazardous Substance List because it is cited by OSHA, ACGIH, DOT and NIOSH.

[SEE GLOSSARY ON PAGE 5.](#)

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention.

Skin Contact

- ▶ Remove contaminated clothing and wash contaminated skin with water.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE LAST PAGE

Hazard Summary

Hazard Rating	NJDHSS	NFPA
HEALTH	2	-
FLAMMABILITY	0	-
REACTIVITY	0	-
STRONG OXIDIZER POISONOUS GASES ARE PRODUCED IN FIRE DOES NOT BURN		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Aluminum Nitrate** can affect you when inhaled and may be absorbed through the skin.
- ▶ **Aluminum Nitrate** can cause skin irritation.
- ▶ Contact can severely irritate and burn the eyes.
- ▶ Inhaling **Aluminum Nitrate** can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.
- ▶ **Aluminum Nitrate** is not combustible, but it is a STRONG OXIDIZER that enhances the combustion of other substances.

Workplace Exposure Limits

The following exposure limits are for *Aluminum*:

OSHA: The legal airborne permissible exposure limit (PEL) is **5 mg/m³** (as *respirable dust*) and **15 mg/m³** (as *total dust*) averaged over an 8-hour workshift.

NIOSH: The recommended airborne exposure limit (REL) is **2 mg/m³** (as the *soluble salt*) averaged over a 10-hour workshift.

ACGIH: The threshold limit value (TLV) is **1 mg/m³** (as the *respirable fraction*) averaged over an 8-hour workshift.

- ▶ The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health and Senior Services Hazardous Substance Fact Sheet, available on the RTK Program website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act and the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Aluminum Nitrate**:

- ▶ **Aluminum Nitrate** can cause skin irritation.
- ▶ Contact can severely irritate and burn the eyes.
- ▶ Inhaling **Aluminum Nitrate** can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Aluminum Nitrate** and can last for months or years:

Cancer Hazard

- ▶ According to the information presently available to the New Jersey Department of Health and Senior Services, **Aluminum Nitrate** has not been tested for its ability to cause cancer in animals.

Reproductive Hazard

- ▶ There is limited evidence that **Aluminum Nitrate** may damage the developing fetus in animals.

Other Effects

- ▶ **Aluminum Nitrate** may affect the lungs, but it is not known whether it causes lung damage.

Medical

Medical Testing

If symptoms develop or overexposure is suspected, the following are recommended:

- ▶ Lung function tests

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- ▶ Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

In addition, the following may be useful or required:

- ▶ Use a vacuum or a wet method to reduce dust during clean-up. DO NOT DRY SWEEP.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Aluminum Nitrate**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend Nitrile and Natural Rubber for gloves, and Tyvek®, or the equivalent, as a protective clothing material.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear eye protection with side shields or goggles.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ Where the potential exists for exposure over **1 mg/m³** (as *Aluminum*), use a NIOSH approved negative pressure, air-purifying, particulate filter respirator with an N, R or P95 filter. More protection is provided by a full facepiece respirator than by a half-mask respirator, and even greater protection is provided by a powered-air purifying respirator.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Aluminum Nitrate**, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.
- ▶ Consider all potential sources of exposure in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- ▶ Where the potential exists for exposure over **10 mg/m³** (as *Aluminum*), use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus or an emergency escape air cylinder.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ **Aluminum Nitrate** is not combustible, but it is a STRONG OXIDIZER that enhances the combustion of other substances.
- ▶ Use water only. DO NOT USE CHEMICAL or CO₂ extinguishing agents.
- ▶ POISONOUS GASES ARE PRODUCED IN FIRE, including *Aluminum Oxide* and *Nitrogen Oxides*.
- ▶ Use water spray to keep fire-exposed containers cool.
- ▶ **Aluminum Nitrate** may ignite combustibles (wood, paper and oil).

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Aluminum Nitrate** is spilled, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Moisten spilled material first or use a HEPA-filter vacuum for clean-up and place into sealed containers for disposal.
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ DO NOT wash into sewer.
- ▶ It may be necessary to contain and dispose of **Aluminum Nitrate** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Aluminum Nitrate** you should be trained on its proper handling and storage.

- ▶ **Aluminum Nitrate** dissolves in WATER to form *Nitric Acid*.
- ▶ **Aluminum Nitrate** is not compatible with COMBUSTIBLE MATERIALS; STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); METALS; METAL SALTS; CYANIDES; THIOCYANATES; ORGANIC MATERIALS and HALOGENATED HYDROCARBONS (such as METHYL CHLORIDE and TRICHLOROETHYLENE).
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from COMBUSTIBLES, WATER and MOISTURE.
- ▶ **Aluminum Nitrate** corrodes METALS in the presence of MOISTURE.

Occupational Health Information Resources

The New Jersey Department of Health and Senior Services, Occupational Health Service, offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health & Senior Services
Right to Know Program
PO Box 368
Trenton, NJ 08625-0368
Phone: 609-984-2202
Fax: 609-984-7407
E-mail: rtk@doh.state.nj.us
Web address: <http://www.nj.gov/health/eoh/rtkweb>

***The Right to Know Hazardous Substance Fact Sheets
are not intended to be copied and sold
for commercial purposes.***

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGLs) are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

The **critical temperature** is the temperature above which a gas cannot be liquefied, regardless of the pressure applied.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database on human health effects that may result from exposure to various chemicals, maintained by federal EPA.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

Protective Action Criteria (PAC) are values established by the Department of Energy and are based on AEGLs and ERPGs. They are used for emergency planning of chemical release events.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Air*), at the same temperature and pressure.

The **vapor pressure** is a force exerted by the vapor in equilibrium with the solid or liquid phase of the same substance. The higher the vapor pressure the higher concentration of the substance in air.



Common Name: **ALUMINUM NITRATE**

Synonyms: Aluminum Trinitrate

CAS No: 13473-90-0

Molecular Formula: Al_3HNO_3

RTK Substance No: 0061

Description: Odorless, colorless to white solid

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
<p>2 - Health</p> <p>0 - Fire</p> <p>0 - Reactivity</p> <p>DOT#: UN 1438</p> <p>ERG Guide #: 140</p> <p>Hazard Class: 5.1 (Oxidizer)</p>	<p>Aluminum Nitrate is not combustible, but it is a STRONG OXIDIZER that enhances the combustion of other substances.</p> <p>Use water only. DO NOT USE CHEMICAL or CO_2 extinguishing agents.</p> <p>POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Aluminum Oxide</i> and <i>Nitrogen Oxides</i>.</p> <p>Use water spray to keep fire-exposed containers cool.</p> <p>Aluminum Nitrate may ignite combustibles (wood, paper and oil).</p>	<p>Aluminum Nitrate dissolves in WATER to form <i>Nitric Acid</i>.</p> <p>Aluminum Nitrate is not compatible with COMBUSTIBLE MATERIALS; STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); METALS; METAL SALTS; CYANIDES; THIOCYANATES; ORGANIC MATERIALS; and HALOGENATED HYDROCARBONS (such as METHYL CHLORIDE and TRICHLOROETHYLENE).</p>

SPILL/LEAKS

Isolation Distance:

Spill: 25 meters (75 feet)

Fire: 800 meters (1/2 mile)

Moisten spilled material first or use a HEPA-filter vacuum for clean-up and place into sealed containers for disposal.

DO NOT wash into sewer.

Neutralize water spills with Sodium Bicarbonate (soda ash).

Aluminum Nitrate is harmful to aquatic life at very low concentrations.

PHYSICAL PROPERTIES

Odor Threshold:	Odorless
Flash Point:	Noncombustible
Specific Gravity:	>1 (water = 1)
Water Solubility:	Soluble
Boiling Point:	302°F (150°C) (Decomposes)
Melting Point:	163°F (73°C)
Molecular Weight:	213

EXPOSURE LIMITS

OSHA: 5 mg/m³ (as *respirable dust*), 8-hr TWA

NIOSH: 2 mg/m³ (as *soluble salt*), 10-hr TWA

ACGIH: 1 mg/m³ (as the *respirable fraction*)
(All the above are for *Aluminum*)

The Protective Action Criteria values are:

PAC-1 = 50 mg/m³ PAC-2 = 350 mg/m³

PAC-3 = 500 mg/m³

PROTECTIVE EQUIPMENT

Gloves:	Nitrile and Natural Rubber
Coveralls:	Tyvek®
Respirator:	>1 mg/m ³ - full facepiece APR with <i>P100 filters</i> >50 mg/m ³ - SCBA

HEALTH EFFECTS

Eyes:	Severe irritation and burns
Skin:	Irritation
Inhalation:	Nose, throat and lung irritation with coughing, wheezing and/or shortness of breath

FIRST AID AND DECONTAMINATION

Remove the person from exposure.
Flush eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn. Seek medical attention.
Remove contaminated clothing and wash contaminated skin with water.
Begin artificial respiration if breathing has stopped and CPR if necessary.
Transfer promptly to a medical facility.