



Right to Know Hazardous Substance Fact Sheet

Common Name: **AMINOETHYLETHANOLAMINE**

Synonyms: A-EA; (2-Hydroxyethyl)Ethylenediamine

Chemical Name: Ethanol, 2-[(2-Aminoethyl)Amino]-

Date: December 1998 Revision: October 2008

CAS Number: 111-41-1

RTK Substance Number: 0074

DOT Number: UN 2735

Description and Use

Aminoethylethanolamine is a clear, colorless, slightly thick liquid with an *Ammonia*-like odor. It is used as a fabric softener, textile additive, lube oil and fuel additive, surfactant, and chelating agent.

Reasons for Citation

- ▶ **Aminoethylethanolamine** is on the Right to Know Hazardous Substance List because it is cited by DOT and NFPA.
- ▶ This chemical is on the Special Health Hazard Substance List.

SEE GLOSSARY ON PAGE 5.

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 30 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention.

Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE PAGE 6

Hazard Summary

Hazard Rating	NJDHSS	NFPA
HEALTH	-	3
FLAMMABILITY	-	1
REACTIVITY	-	0
CORROSIVE POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Aminoethylethanolamine** can affect you when inhaled and by passing through the skin
- ▶ Contact can irritate and may burn the skin.
- ▶ **Aminoethylethanolamine** can irritate and burn the eyes, leading to permanent damage.
- ▶ Inhaling **Aminoethylethanolamine** can irritate the nose, throat and lungs.
- ▶ **Aminoethylethanolamine** may cause a skin allergy and an asthma-like allergy

Workplace Exposure Limits

No occupational exposure limits have been established for **Aminoethylethanolamine**. However, it may pose a health risk. Always follow safe work practices.

- ▶ It should be recognized that **Aminoethylethanolamine** can be absorbed through your skin, thereby increasing your exposure.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health and Senior Services Hazardous Substance Fact Sheet, available on the RTK Program website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to

Aminoethylethanolamine:

- ▶ Contact can irritate and may burn the skin.
- ▶ **Aminoethylethanolamine** can irritate and burn the eyes, leading to permanent damage.
- ▶ Inhaling **Aminoethylethanolamine** can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Aminoethylethanolamine** and can last for months or years:

Cancer Hazard

- ▶ According to the information presently available to the New Jersey Department of Health and Senior Services, **Aminoethylethanolamine** has not been tested for its ability to cause cancer in animals.

Reproductive Hazard

- ▶ There is limited evidence that **Aminoethylethanolamine** may damage the developing fetus in animals.

Other Effects

- ▶ **Aminoethylethanolamine** may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- ▶ **Aminoethylethanolamine** may cause an asthma-like allergy. Future exposure can cause asthma attacks with shortness of breath, wheezing, coughing, and/or chest tightness.

Medical

Medical Testing

If symptoms develop or overexposure is suspected, the following are recommended:

- ▶ Evaluation by a qualified allergist can help diagnose skin allergy.
- ▶ Lung function tests. The results may be normal if the person is not having an attack at the time of the test.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- ▶ Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Aminoethylethanolamine**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend Silver Shield®/4H® and Barrier® for gloves and Tychem® BR, LV, Responder®, and TK; Zytron® 500; ONESuit® TEC; and Trelchem® HPS and VPS, or the equivalent, as protective materials for *Diethylamine*.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- ▶ Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ Where the potential for overexposure exists, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ **Aminoethylethanolamine** may burn, but does not readily ignite.
- ▶ Use dry chemical, CO₂, water spray, alcohol-resistant foam or other foam as extinguishing agents.
- ▶ Using water or foam directly on **Aminoethylethanolamine** may cause frothing and solid streams of water may be ineffective.
- ▶ POISONOUS GASES ARE PRODUCED IN FIRE, including *Nitrogen Oxides*.
- ▶ CONTAINERS MAY EXPLODE IN FIRE.
- ▶ Use water spray to keep fire-exposed containers cool.

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Aminoethylethanolamine** is spilled or leaked, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Absorb liquids in vermiculite, dry sand, earth, or a similar material and place into sealed containers.
- ▶ DO NOT use organic absorbants (such as woodchips or sawdust).
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ DO NOT wash into sewer.
- ▶ It may be necessary to contain and dispose of **Aminoethylethanolamine** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Aminoethylethanolamine** you should be trained on its proper handling and storage.

- ▶ **Aminoethylethanolamine** reacts violently with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); and CELLULOSE NITRATE.
- ▶ **Aminoethylethanolamine** is not compatible with HALOGENATED SOLVENTS (such as TRICHLOROETHANE and METHYLENE CHLORIDE); NITRITES; ALCOHOLS; ALDEHYDES; CRESOLS; EPICHLOROHYDRIN; ISOCYANATES; KETONES; PHENOL; and VINYL ACETATE.
- ▶ In the presence of ALUMINUM and HEAT, explosive and flammable *Hydrogen gas* may be formed.
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from HEAT and MOISTURE.
- ▶ DO NOT store or use **Aminoethylethanolamine** in containers or piping with COPPER, COPPER ALLOYS, BRASS, or BRONZE as corrosion will occur.
- ▶ Sources of ignition, such as smoking and open flames, are prohibited where **Aminoethylethanolamine** is used, handled, or stored in a manner that could create a potential fire or explosion hazard.
- ▶ Store **Aminoethylethanolamine** under a dry, inert gas blanket, such as *Nitrogen*, to prevent contamination from air and water.

Occupational Health Information Resources

The New Jersey Department of Health and Senior Services, Occupational Health Service, offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health & Senior Services
 Right to Know Program
 PO Box 368
 Trenton, NJ 08625-0368
 Phone: 609-984-2202
 Fax: 609-984-7407
 E-mail: rtk@doh.state.nj.us
 Web address: <http://www.nj.gov/health/eoh/rtkweb>

The Right to Know Hazardous Substance Fact Sheets are not intended to be copied and sold for commercial purposes.

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGs) are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database on human health effects that may result from exposure to various chemicals, maintained by federal EPA.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

Protective Action Criteria (PAC) are values established by the Department of Energy and are based on AEGs and ERPGs. They are used for emergency planning of chemical release events.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a force exerted by the vapor in equilibrium with the solid or liquid phase of the same substance. The higher the vapor pressure the higher concentration of the substance in air.



Common Name: **AMINOETHYLETHANOLAMINE**

Synonyms: A-EA; (2-Hydroxyethyl)Ethylenediamine

CAS No: 111-41-1

Molecular Formula: C₄H₁₂N₂O

RTK Substance No: 0074

Description: Clear, colorless, slightly thick liquid with an *Ammonia*-like odor

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
<p>3 - Health</p> <p>1 - Fire</p> <p>0 - Reactivity</p> <p>DOT#: UN 2735</p> <p>ERG Guide #: 153</p> <p>Hazard Class: 8 (Corrosive)</p>	<p>May burn, but does not readily ignite.</p> <p>Use dry chemical, CO₂, water spray, alcohol-resistant foam or other foam as extinguishing agents.</p> <p>Using water or foam directly on Aminoethylethanolamine may cause frothing and solid streams of water may be ineffective.</p> <p>POISONOUS GASES ARE PRODUCED IN FIRE, including Nitrogen Oxides.</p> <p>CONTAINERS MAY EXPLODE IN FIRE.</p> <p>Use water spray to keep fire-exposed containers cool.</p>	<p>Aminoethylethanolamine reacts violently with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC); and CELLULOSE NITRATE.</p> <p>Aminoethylethanolamine is not compatible with HALOGENATED SOLVENTS (such as TRICHLOROETHANE and METHYLENE CHLORIDE); NITRITES; ALCOHOLS; ALDEHYDES; CRESOLS; EPICHLOROHYDRIN; ISOCYANATES; KETONES; PHENOL; and VINYL ACETATE.</p> <p>In the presence of ALUMINUM and HEAT, explosive and flammable Hydrogen gas may be formed.</p>

SPILL/LEAKS

Isolation Distance:

Small Spill: 30 meters (100 feet)

Large Spill: 60 meters (200 feet)

Fire: 800 meters (1/2 mile)

Absorb liquids in vermiculite, dry sand, earth, or a similar material and place into sealed containers.

DO NOT wash into sewer.

PHYSICAL PROPERTIES

Odor Threshold:	<i>Ammonia</i> -like
Flash Point:	270°F (132°C)
LEL:	1%
UEL:	8%
Auto Ignition Temp:	695°F (368°C)
Vapor Density:	3.6 (air = 1)
Vapor Pressure:	<0.01 mm Hg at 68°F (20°C)
Specific Gravity:	1 (water = 1)
Water Solubility:	Soluble
Boiling Point:	470°F (243°C)
Freezing Point:	-49°F (-45°C)
pH:	11.5
Molecular Weight:	104

EXPOSURE LIMITS

The Protective Action Criteria values are:

PAC-1 = 35 mg/m³

PAC-2 = 250 mg/m³

PAC-3 = 500 mg/m³

PROTECTIVE EQUIPMENT

Gloves:	Silver Shield®/4H® and Barrier® (>4-hr breakthrough)
Coveralls:	Tychem® BR, LV, Responder®, and TK; Zytron® 500; ONESuit® TEC; and Trelchem® HPS and VPS (>8-hr breakthrough for <i>Diethylamine</i>)
Respirator:	Supplied air or SCBA

HEALTH EFFECTS

Eyes:	Irritation and burns
Skin:	Irritation and burns
Inhalation:	Nose, throat and lung irritation with coughing, wheezing and shortness of breath.

FIRST AID AND DECONTAMINATION

Remove the person from exposure.
Flush eyes with large amounts of water for at least 30 minutes. Remove contact lenses if worn. Seek medical attention
Quickly remove contaminated clothing and wash contaminated skin with large amounts of water.
Begin artificial respiration if breathing has stopped and CPR if necessary.
Transfer promptly to a medical facility