

ealth Hazardous Substance Fact Sheet

Common Name: DIMETHYLCARBAMOYL CHLORIDE

- Synonyms: DMCC; Chloroformic Acid Dimethylamide
- Chemical Name: Carbamic Chloride, Dimethyl-
- Date: December 1998 Revision: July 2008

Description and Use

Dimethylcarbamoyl Chloride is a clear, colorless liquid with an unpleasant odor. It is used as a chemical intermediate in making pesticides, pharmaceuticals and dyes.

Reasons for Citation

- Dimethylcarbamoyl Chloride is on the Right to Know Hazardous Substance List because it is cited by ACGIH, DOT, NIOSH, NTP, DEP, IARC and EPA.
- This chemical is on the Special Health Hazard Substance List.

SEE GLOSSARY ON PAGE 5.

Eye Contact

FIRST AID

Immediately flush with large amounts of water for at least 30 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention immediately.

Skin Contact

 Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water. Seek medical attention.

Inhalation

- ▶ Remove the person from exposure.
- Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222 CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

CAS Number:	79-44-7
RTK Substance Number:	0746
DOT Number:	UN 2262

EMERGENCY RESPONDERS >>>> SEE BACK PAGE

Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	3	-
FLAMMABILITY	2	-
REACTIVITY	1	-

CARCINOGEN AND CORROSIVE COMBUSTIBLE POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE DO NOT USE WATER

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- Dimethylcarbamoyl Chloride can affect you when inhaled and may be absorbed through the skin.
- Dimethylcarbamoyl Chloride should be handled as a CARCINOGEN and MUTAGEN--WITH EXTREME CAUTION.
- Contact can irritate and burn the skin and eyes.
- Inhaling Dimethylcarbamoyl Chloride can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.
- ► Exposure to **Dimethylcarbamoyl Chloride** can cause headache, nausea and vomiting.
- Dimethylcarbamoyl Chloride may affect the liver.

Workplace Exposure Limits

- NIOSH: Recommends that exposure to occupational carcinogens be limited to the lowest feasible concentration.
- ACGIH: The threshold limit value (TLV) is **0.005 ppm** averaged over an 8-hour workshift.
- Dimethylcarbamoyl Chloride is a PROBABLE CARCINOGEN in humans. There may be <u>no</u> safe level of exposure to a carcinogen, so all contact should be reduced to the lowest possible level.
- The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

Determining Your Exposure

- Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ► For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ➤ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Dimethylcarbamoyl Chloride**:

- Contact can irritate and burn the skin and eyes.
- Inhaling Dimethylcarbamoyl Chloride can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.
- ► Exposure to **Dimethylcarbamoyl Chloride** can cause headache, nausea and vomiting.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Dimethylcarbamoyl Chloride** and can last for months or years:

Cancer Hazard

- Dimethylcarbamoyl Chloride is a PROBABLE CARCINOGEN in humans since it has been shown to cause nose and skin cancer in animals.
- Many scientists believe there is no safe level of exposure to a carcinogen. Such substance may also have the potential for causing reproductive damage in humans.

Reproductive Hazard

According to the information presently available to the New Jersey Department of Health, **Dimethylcarbamoyl Chloride** has not been tested for its ability to affect reproduction.

Other Effects

- Dimethylcarbamoyl Chloride can irritate the lungs. Repeated exposure may cause bronchitis to develop with coughing, phlegm, and/or shortness of breath.
- ► Dimethylcarbamoyl Chloride may affect the liver.

Medical

Medical Testing

If symptoms develop or overexposure is suspected, the following are recommended:

- Lung function tests
- Liver function tests

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.
- More than light alcohol consumption can cause liver damage. Drinking alcohol may increase the liver damage caused by Dimethylcarbamoyl Chloride.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at <u>www.cdc.gov/niosh/topics/ctrlbanding/</u>.

The following work practices are also recommended:

- ► Label process containers.
- ▶ Provide employees with hazard information and training.
- Monitor airborne chemical concentrations.
- Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- Wash or shower if skin comes in contact with a hazardous material.
- Always wash at the end of the workshift.
- Change into clean clothing if clothing becomes contaminated.
- ► Do not take contaminated clothing home.
- Get special training to wash contaminated clothing.
- Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ➤ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- Avoid skin contact with Dimethylcarbamoyl Chloride. Wear personal protective equipment made from material that can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- Safety equipment manufacturers recommend Silver Shield®/4H® for gloves and DuPont Tychem® CSM, Responder®, and TK, or the equivalent, as protective materials for *known carcinogens*.
- All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- ► Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

► Where the potential exists for exposure over 0.005 ppm, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positivepressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ► Dimethylcarbamoyl Chloride is a COMBUSTIBLE LIQUID.
- ► Use dry chemical, CO₂, alcohol-resistant foam or other foam extinguishing agents.
- DO NOT USE WATER.
- ► POISONOUS GASES ARE PRODUCED IN FIRE, including *Hydrogen Chloride* and *Nitrogen Oxides*.
- CONTAINERS MAY EXPLODE IN FIRE.
- ► Use water spray only to keep fire-exposed containers cool as water will decompose **Dimethylcarbamoyl Chloride** to form toxic *Hydrogen Chloride* and *Dimethylamine*.

DIMETHYLCARBAMOYL CHLORIDE

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Dimethylcarbamoyl Chloride** is spilled or leaked, take the following steps:

- Evacuate personnel and secure and control entrance to the area.
- Eliminate all ignition sources.
- Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.
- ► DO NOT USE WATER OR WET METHOD.
- ► Ventilate area after clean-up is complete.
- ► DO NOT wash into sewer.
- It may be necessary to contain and dispose of Dimethylcarbamoyl Chloride as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Dimethylcarbamoyl Chloride** you should be trained on its proper handling and storage.

- Dimethylcarbamoyl Chloride will react with WATER, STEAM and MOISTURE to produce toxic Hydrogen Chloride and Dimethylamine.
- Dimethylcarbamoyl Chloride reacts vigorously or explosively if mixed with DIISOPROPYL ETHER or other ETHERS in the presence of small amounts of METAL SALTS.
- Dimethylcarbamoyl Chloride is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); ALCOHOLS; STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); and AMINES.
- Store in tightly closed containers in a cool, well-ventilated area away from METALS (such as STEEL and GALVANIZED STEEL/ZINC) as flammable and explosive Hydrogen gas may form.
- Sources of ignition, such as smoking and open flames, are prohibited where **Dimethylcarbamoyl Chloride** is used, handled, or stored in a manner that could create a potential fire or explosion hazard.
- Use only non-sparking tools and equipment, especially when opening and closing containers of Dimethylcarbamoyl Chloride.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health Right to Know PO Box 368 Trenton, NJ 08625-0368 Phone: 609-984-2202 Fax: 609-984-7407 E-mail: rtk@doh.state.nj.us Web address: http://www.nj.gov/health/eoh/rtkweb

The Right to Know Hazardous Substance Fact Sheets are not intended to be copied and sold for commercial purposes.

DIMETHYLCARBAMOYL CHLORIDE

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGLs) are established by the EPA. They describe the risk to humans resulting from once-in-a lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A carcinogen is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A combustible substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values are intended to provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A fetus is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database maintained by federal EPA. The database contains information on human health effects that may result from exposure to various chemicals in the environment. **LEL** or **Lower Explosive Limit**, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

PIH is a DOT designation for chemicals which are Poison Inhalation Hazards.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or **Upper Explosive Limit** is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.



Common Name: DIMETHYLCARBAMOYL CHLORIDE

Synonyms: DMCC; Chloroformic Acid Dimethylamide CAS No: 79-44-7 Molecular Formula: C_3H_6CINO RTK Substance No: 0746 Description: Clear, colorless liquid with an unpleasant odor

HAZARD DATA		
Hazard Rating	Firefighting	Reactivity
3 - Health	Dimethylcarbamoyl Chloride is a COMBUSTIBLE LIQUID.	Dimethylcarbamoyl Chloride will react with WATER, STEAM and MOISTURE to produce toxic
2 - Fire	Use dry chemical, CO_2 , alcohol-resistant foam or other	Hydrogen Chloride and Dimethylamine.
1 - Reactivity	foam extinguishing agents.	Dimethylcarbamoyl Chloride reacts vigorously or
DOT#: UN 2262 ERG Guide #: 156 Hazard Class: 8 (Corrosive)	DO NOT USE WATER. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Hydrogen Chloride</i> and <i>Nitrogen Oxides</i> . CONTAINERS MAY EXPLODE IN FIRE. Use water spray only to keep fire-exposed containers cool as water will decompose Dimethylcarbamoyl Chloride to form toxic <i>Hydrogen Chloride</i> and <i>Dimethylamine</i> .	explosively if mixed with DIISOPROPYL ETHER or other ETHERS in the presence of small amounts of METAL SALTS. Dimethylcarbamoyl Chloride is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); ALCOHOLS; STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); and AMINES.

SPILL/LEAKS

Isolation Distance:

Small Spill: 60 meters (200 feet)

Large Spill: 270 meters (900 feet)

Fire: 800 meters (1/2 mile)

Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers. DO NOT USE WATER OR WET METHOD. DO NOT wash into sewer.

EXPOSURE LIMITS

OSHA:NoneNIOSH:Lowest feasible concentrationACGIH:0.005 ppm, 8-hr TWAIDLH:None

HEALTH EFFECTS	
Eyes:	Irritation and burns
Skin:	Irritation and burns
Inhalation:	Nose, throat and lung irritation with coughing, wheezing and shortness of breath
	Headache, nausea and vomiting
Chronic:	Cancer (nose and skin) in animals

PHYSICAL PROPERTIES

Odor Threshold:	Unpleasant odor
Flash Point:	155°F (68°C)
Vapor Density:	3.7 (air = 1)
Vapor Pressure:	2.5 mm Hg at 77°F (25°C)
Specific Gravity:	1.2 (water = 1)
Water Solubility:	Reactive/Decomposes
Boiling Point:	329° to 333°F (165° to 167°C)
Melting Point:	-27°F (-33°C)
Molecular Weight:	107.6

	PROTECTIVE EQUIPMENT
Gloves:	Silver Shield®/4H®
Coveralls:	DuPont Tychem® CSM, Responder®, and TK (for <i>known carcinogens</i>)
Respirator:	>0.005 ppm - Supplied air

FIRST AID AND DECONTAMINATION

Remove the person from exposure.

Flush eyes with large amounts of water for at least 30 minutes. Remove contact lenses if worn. Seek medical attention immediately.

Quickly remove contaminated clothing and wash contaminated skin with large amounts of soap and water. Seek medical attention.

Begin artificial respiration if breathing has stopped and CPR if necessary. **Transfer** promptly to a medical facility.