

# **Right to Know**

# **Hazardous Substance Fact Sheet**

Common Name: PARAOXON

Synonyms: Phosphacol; Ester 25; Eticol; Fosfakol; Mintacol;

Miotisal A; Soluglaucit

Chemical Name: Phosphoric Acid, Diethyl p-Nitrophenyl Ester

Date: December 2022 Revision: June 2023

# **Description and Use**

**Paraoxon** is an odorless, reddish-yellow oil. It is used as an *Organophosphate* insecticide. It has also been used as a medication to treat glaucoma.

# **Reason for Citation**

Paraoxon is on the Right to Know Hazardous Substance List because it is cited by DOT and EPA.

#### SEE GLOSSARY ON PAGE 5

## **FIRST AID**

# **Eye Contact**

► Immediately flush with large amounts of water for at least 15 minutes, occasionally lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention immediately.

#### **Skin Contact**

- Quickly remove contaminated clothing. Immediately wash area with large amounts of soap and water. Seek medical attention immediately.
- ▶ Shampoo hair promptly if contaminated.

## Inhalation

- ▶ Remove the person from exposure.
- Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ► Transfer promptly to a medical facility.
- Medical observation is required for several days as symptoms may be delayed.

# **EMERGENCY NUMBERS**

Poison Control: 1-800-222-1222 CHEMTREC: 1-800-424-9300 NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

CAS Number: 311-45-5

RTK Number: 1457

DOT Number: UN 3018
DOT Hazard: 6.1 (poison)

# **Hazard Summary**

**EMERGENCY RESPONDERS >>>> SEE BACK PAGE** 

Hazard Rating	NJDOH	NFPA	
HEALTH	4	-	
FLAMMABILITY	1	_	
REACTIVITY	1	-	

COMBUSTIBLE

POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE

Hazard Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ► **Paraoxon** can affect you when breathed in and quickly enters the body by passing through the skin.
- ▶ Breathing **Paraoxon** can irritate the nose, throat and lungs.
- ► Exposure can cause *Organophosphate poisoning*. Symptoms develop quickly and can be fatal. Symptoms include headache, dizziness, blurred vision, chest tightness, twitching, loss of coordination, convulsions, coma and death.
- High or repeated exposure can damage the nervous system causing numbness, pins and needles, and weakness in the hands and feet.
- Repeated exposure may cause personality changes of depression, anxiety or irritability.
- ▶ Liquid formulations containing solvents may be flammable.

# **Workplace Exposure Limits**

No occupational exposure limits have been established for **Paraoxon**. This does not mean that this substance is not harmful. Safe work practices should always be followed.

► It should be recognized that **Paraoxon** can be absorbed through your skin, thereby increasing your exposure.

PARAOXON page 2 of 6

# **Determining Exposure**

- Read the product Material Safety Data Sheet (MSDS) and label to determine ingredients and important safety and health information.
- Read the New Jersey Department of Health Hazardous Substance Fact Sheets on the chemicals in the product at <a href="http://nj.gov/health/workplacehealthandsafety/right-to-know/">http://nj.gov/health/workplacehealthandsafety/right-to-know/</a> or in your facility's Right to Know Central File or Hazard Communication Standard file.
- Public workers in New Jersey have a right to information about the chemicals with which they work under the New Jersey Worker and Community Right to Know Act and the Public Employees Occupational Safety and Health Act (PEOSHA). Private workers have the same right under the federal Occupational Safety and Health Act (OSHA).
- ► The New Jersey Worker and Community Right to Know Act and the PEOSH Hazard Communication Standard require most employers to label chemicals in the workplace and require public employers to provide employees with information and training on chemical hazards and controls. The federal OSHA Hazard Communication Standard requires private employers to provide similar information and training to employees.

# **Health Hazard Information**

Below is a summary of available information regarding health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors affect individual susceptibility.

# **Acute Health Effects**

The following acute (short-term) health effects may occur immediately or shortly after exposure:

- ▶ Breathing **Paraoxon** can irritate the nose, throat and lungs.
- ▶ Organophosphate pesticides can cause dermal sensitization.
- Exposure can cause Organophosphate poisoning. Symptoms develop quickly and can be fatal. Symptoms include headache, dizziness, blurred vision, chest tightness, twitching, loss of coordination, convulsions, coma and death.

## Other Health Effects

The following chronic (long-term) health effects can occur at some time after exposure and can last for months or years:

# Cancer Hazard

According to the information presently available to the New Jersey Department of Health, Paraoxon has not been tested for its ability to cause cancer in animals.

# Reproductive Hazard

 According to the information presently available to the New Jersey Department of Health, Paraoxon has not been tested for its ability to affect reproduction.

#### Other Effects

- High or repeated exposure can damage the nervous system causing numbness, pins and needles, and weakness in the hands and feet.
- Repeated exposure may cause personality changes of depression, anxiety or irritability.

# Medical

Medical evaluations should include a detailed history of past and present symptoms and a physical exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of test results. You have a right to your medical information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

#### **Medical Testing**

Before employment and regularly thereafter, the following are recommended:

- ➤ Test for *Cholinesterase* levels in plasma and red blood cells. Once exposure stops, *Cholinesterase* levels will return to normal in 1-2 weeks in plasma and 1-3 months in red blood cells.
- ▶ When *Cholinesterase* levels are 25 % or more below preemployment levels, poisoning risk increases, even if reduced levels are still in the "normal" range.
- Reassignment to work not involving Organophosphate or Carbamate pesticides is recommended until enzyme levels recover.

In addition, if symptoms develop, the following is recommended:

- Evaluate for brain effects such as changes in memory, concentration, sleeping, mood, headaches and fatigue.
- Consider evaluating the central, autonomic and peripheral nervous systems, with follow-up testing if results are positive or borderline.
- ► Consider neurobehavioral, nerve conduction and urinary enzyme testing.

## **Mixed Exposures**

► There may be greater risk of experiencing effects if there is also exposure to other chemicals that affect *Cholinesterase* levels (*Organophosphates*, *Carbamates*).

# **Workplace Controls and Practices**

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and

PARAOXON page 3 of 6

(3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following practices are recommended:

- ▶ Label process containers.
- Train and inform employees about hazards.
- Monitor airborne chemical concentrations.
- ► Automatically transfer combustible and flammable liquids from storage to process containers.
- Use engineering controls at elevated levels of exposure.
- Provide eye wash fountains and emergency showers.
- Wash skin after contact with a hazardous material.
- Wash at the end of the work shift.
- Do not wear clothing once it becomes contaminated.
- Do not take contaminated clothing home.
- Special training is required to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

## In addition:

- Special controls and practices for occupational exposure to pesticides are required by the Worker Protection Standard (40 CFR Part 170).
- ► For more information, contact the New Jersey Department of Environmental Protection Pesticide Control Program (<a href="http://www.nj.gov/dep/enforcement/pcp/index.htm">http://www.nj.gov/dep/enforcement/pcp/index.htm</a>).

# **Personal Protective Equipment**

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment. All personal protective equipment (including suits, gloves, footwear and headgear) should be clean, available each day and put on before work.

Consult safety equipment suppliers and manufacturers for specific recommendations. The following recommendations are only guidelines and may not apply to every situation:

# **Gloves and Clothing**

- Do not use leather. This substance is absorbed into leather and cannot be removed by cleaning.
- ► Avoid skin contact with **Paraoxon**. Wear personal protective equipment made from material that cannot be permeated or degraded by this substance.
- Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.

- ► The recommended glove materials for *Organophosphorus* compounds are Nitrile and Neoprene.
- ► The recommended protective clothing materials are Tychem® BR, CSM and TK, or the equivalent.

#### **Eye Protection**

Eye protection is included in the recommended respiratory protection.

## **Respiratory Protection**

Improper use of respirators is dangerous. Respirators only should be used in accordance with a written program that takes into account workplace conditions, worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134). Only use NIOSH-approved respirators.

- For outdoor use, check with your supervisor and your safety equipment supplier regarding the appropriate respiratory equipment.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect the chemical substance, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator.
- Consider all potential exposure sources. You may need a combination of filters, pre-filters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- Where the potential for exposure exists, use a supplied-air respirator with a full facepiece operated in a pressuredemand or other positive-pressure mode. For increased protection use in combination with an auxiliary selfcontained breathing apparatus operated in a pressuredemand or other positive-pressure mode.

# **Fire Hazards**

Employees who are expected to fight fires must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ This substance is COMBUSTIBLE.
- ▶ Paraoxon may burn but does not readily ignite.
- ► Use dry chemical, CO<sub>2</sub>, alcohol or polymer foam extinguishers, as water may not be effective in fighting fires
- ▶ Liquid formulations containing solvents may be flammable.
- ► POISONOUS GASES ARE PRODUCED IN FIRE, including *Oxides of Nitrogen* and *Phosphorus*.
- ► CONTAINERS MAY EXPLODE IN FIRE.
- ▶ Use water spray to keep fire-exposed containers cool.

# Spills and Emergencies

Employees who are required to clean-up spills or leaks must be properly trained and equipped. The OSHA Hazardous PARAOXON page 4 of 6

Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

It may be necessary to contain and dispose of this substance as HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

In case of accidental release:

- Evacuate personnel.
- Secure and control entrance to the area.
- ▶ If it is safe to do so, remove potential ignition sources.
- ► Absorb liquids in vermiculite, dry sand, earth or similar material and deposit in sealed containers.
- Do NOT allow this substance to enter waterways, including sewers, as it is very toxic to aquatic life with long-lasting effects.
- ▶ Ventilate and wash area after clean-up is complete.

# **Handling and Storage**

Prior to working with this substance, employees should be trained on proper handling and storage.

- Paraoxon must be stored to avoid contact with ENDRIN since violent reactions occur.
- Paraoxon is not compatible with STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE); and OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE).
- Store in tightly closed containers in a cool, well-ventilated area
- Sources of ignition, such as smoking and open flames, are prohibited where this substance is used, handled, or stored in a manner that could create a potential fire or explosion hazard.

# **Occupational Health Resources**

The New Jersey Department of Health's Occupational Health Service offers information, resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations, among other services.

## For more information, please contact:

New Jersey Department of Health - Right to Know

PO Box 368

Trenton, NJ 08625-0368

Phone: 609-984-2202 Fax: 609-984-7407 E-mail: rtk@doh.nj.gov

Web address:

http://nj.gov/health/workplacehealthandsafety/right-to-know/

The Right to Know Hazardous Substance Fact Sheets are not intended to be copied and sold for commercial purposes.

PARAOXON page 5 of 6

## **GLOSSARY**

**ACGIH** is the American Conference of Governmental Industrial Hygienists. It determines Threshold Limit Values (TLVs).

A carcinogen is a substance that causes cancer.

The **CAS number** is the unique, identifying number assigned by the Chemical Abstracts Service to a specific chemical.

**CFR** is the Code of Federal Regulations, which are the regulations of the United States government.

A combustible substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that can weaken or destroy human skin or chemical containers.

**DOT** is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

**EPA** is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

**ERG** is the Emergency Response Guidebook, a resource for responding to chemical emergencies during transportation.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

IARC is the International Agency for Research on Cancer.

**IDLH** is the level of substance which is Immediately Dangerous to Life or Health.

IRIS is the EPA's Integrated Risk Information System.

**LEL** or **Lower Explosive Limit**, is the lowest concentration of a substance in air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that changes the genetic material of cells, and can lead to birth defects, miscarriages, or cancer.

**NJDEP** is the New Jersey Department of Environmental protection.

**NFPA** is the National Fire Protection Association. It classifies substances according to the risk of fire and explosion.

**NIOSH** is the National Institute for Occupational Safety and Health. It tests equipment, approves respirators, studies workplace hazards, and proposes standards to OSHA.

**NTP** is the National Toxicology Program, which tests chemicals and reviews evidence to determine carcinogenicity.

**OSHA** is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

**PEOSHA** is the New Jersey Public Employees Occupational Safety and Health Act.

**PEL** is the permissible exposure. It is established by OSHA.

**PIH** stands for Poison Inhalation Hazard. This classification is established by the DOT.

**ppm** means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

**Protective Action Criteria** (PAC) are values established by the Department of Energy for chemical emergencies.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

**REL** is the recommended exposure limit by NIOSH.

**STEL** is a Short-Term Exposure Limit, which should never be exceeded during the work day.

**TLV** is the Threshold Limit Value, an exposure limit for airborne concentrations.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

**UEL** or **Upper Explosive Limit** is the concentration of a substance in air above which there is too much fuel to continue an explosion.



# **RIGHT TO KNOW** HAZARDOUS SUBSTANCE FACT SHEET



Common Name: PARAOXON

Phosphacol; Ester 25; Eticol; Fosfakol; Mintacol; Miotisal A; Soluglaucit Synonyms:

CAS Number: 311-45-5  $C_{10}H_{14}NO_6P$ Molecular Formula: RTK Number: 1457

Description: Odorless, reddish-yellow oil

HAZARD DATA			
Hazard Ratir	ng	Firefighting	Reactivity
Health:	4	Use dry chemical, CO <sub>2</sub> , alcohol or polymer foam	Paraoxon is not compatible with STRONG
Fire:	1	extinguishers, as water may not be effective in fighting fires.	BASES (such as SODIUM HYDROXIDE
Reactivity:	1	POISONOUS GASES ARE PRODUCED IN FIRE,	and POTASSIUM HYDROXIDE); and OXIDIZING AGENTS (such as
DOT #:	UN 3018	including Oxides of <i>Nitrogen</i> and <i>Phosphorus</i> .	PERCHLORATES, PEROXIDES,
ERG #:	152	CONTAINERS MAY EXPLODE IN FIRE.	PERMANGANATES, CHLORATES,
DOT Hazard:	6.1 (poison)	Use water spray to keep fire-exposed containers cool.	NITRATES, CHLORINE, BROMINE and FLUORINE).

# SPILLS/LEAKS

**Isolation Distances:** 

Liquid Spill: 50 meters (150 feet) Solid Spill: 25 meters (75 feet) Fire: 800 meters (1/2 mile)

Evacuate personnel.

Secure and control entrance to the area.

If it is safe to do so, remove potential ignition sources. Absorb liquids in vermiculite, dry sand, earth or similar material and deposit in sealed containers.

Do NOT allow this substance to enter waterways, including sewers, as it is very toxic to aquatic life with long-lasting effects.

Ventilate and wash area after clean-up is complete.

# **PHYSICAL PROPERTIES**

Molecular Weight: 275.22

1.274 at 20° C (68° F) at 760 mm Hg **Specific Gravity** 

**Boiling Point** 170° C (338° F) at 1mmHg

Water Solubility: Slightly soluble

# **EXPOSURE LIMITS**

There are no occupational exposure limits to this substance.

# PROTECTIVE EQUIPMENT

Gloves: Nitrile and Neoprene Coverall: Tychem® BR, CSM, and TK

Respirator: Supplied-air, full facepiece, pressuredemand or another positive-pressure

mode

# **ACUTE HEALTH EFFECTS**

Eyes: Blurred vision Skin: No known effects

Inhalation: Headache, dizziness, blurred vision, chest

tightness, twitching, loss of coordination,

convulsions, coma, death

# FIRST AID AND DECONTAMINATION

Immediately flush eyes with large amounts of water for at least 15 minutes.

Quickly remove contaminated clothing. Immediately wash area with large amounts of soap and water.

Shampoo hair promptly if contaminated.

Remove the person from exposure.

Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.

Transfer promptly to a medical facility.

Medical observation is required for several days as

symptoms may be delayed.