

New Jersey Department of Health and Senior Services

HAZARDOUS SUBSTANCE FACT SHEET

Common Name: TEPP

CAS Number:	107-49-3	
DOT Number:	NA 2783 (Solid)	
	NA 3018 (Liquid)	

HAZARD SUMMARY

- * **TEPP** can affect you when breathed in and quickly enters the body by passing through the skin.
- * Exposure to **TEPP** can cause rapid, FATAL *Organophosphate poisoning* with headache, sweating, nausea and vomiting, diarrhea, loss of coordination, and death.
- * Breathing **TEPP** may irritate the lungs causing coughing and/or shortness of breath. Higher exposures can cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency, with severe shortness of breath.
- * Repeated exposure may cause personality changes of depression, anxiety or irritability.
- * Very high exposure may affect the nervous system.

IDENTIFICATION

TEPP is a colorless to amber-colored liquid or solid with a faint fruity odor. It is an insecticide and rodenticide.

REASON FOR CITATION

- * **TEPP** is on the Hazardous Substance List because it is regulated by OSHA and cited by ACGIH, DOT, NIOSH and EPA.
- * Definitions are provided on page 5.

HOW TO DETERMINE IF YOU ARE BEING EXPOSED

The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information and training concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard, 1910.1200, requires private employers to provide similar training and information to their employees.

* Exposure to hazardous substances should be routinely evaluated. This may include collecting personal and area air samples. You can obtain copies of sampling results from your employer. You have a legal right to this information under OSHA 1910.1020.

* If you think you are experiencing any work-related health problems, see a doctor trained to recognize occupational diseases. Take this Fact Sheet with you.

WORKPLACE EXPOSURE LIMITS

- OSHA: The legal airborne permissible exposure limit (PEL) is 0.05 mg/m^3 averaged over an 8-hour workshift.
- NIOSH: The recommended airborne exposure limit is 0.05 mg/m^3 averaged over a 10-hour workshift.
- ACGIH: The recommended airborne exposure limit is 0.05 mg/m^3 averaged over an 8-hour workshift.
- * The above exposure limits are for <u>air levels only</u>. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

WAYS OF REDUCING EXPOSURE

- * Where possible, enclose operations and use local exhaust ventilation at the site of chemical release. If local exhaust ventilation or enclosure is not used, respirators should be worn.
- * Wear protective work clothing.
- * Wash thoroughly <u>immediately</u> after exposure to **TEPP** and at the end of the workshift.
- * Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards of **TEPP** to potentially exposed workers.

This Fact Sheet is a summary source of information of <u>all</u> <u>potential</u> and most severe health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

HEALTH HAZARD INFORMATION

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **TEPP**:

- * Exposure to **TEPP** can cause rapid, FATAL, *Organophosphate poisoning* with headache, dizziness, blurred vision, tightness in the chest, sweating, nausea and vomiting, diarrhea, muscle twitching, loss of coordination, convulsions, coma and death.
- * Breathing **TEPP** can irritate the lungs causing coughing and/or shortness of breath. Higher exposures can cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency, with severe shortness of breath.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **TEPP** and can last for months or years:

Cancer Hazard

* According to the information presently available to the New Jersey Department of Health and Senior Services, **TEPP** has not been tested for its ability to cause cancer in animals.

Reproductive Hazard

* According to the information presently available to the New Jersey Department of Health and Senior Services, **TEPP** has not been tested for its ability to affect reproduction.

Other Long-Term Effects

- * Repeated exposure may cause personality changes of depression, anxiety or irritability.
- * Very high exposure may affect the nervous system.

MEDICAL

Medical Testing

Before employment and at regular times after that, the following are recommended:

* Plasma and red blood cell cholinesterase levels (tests for the enzyme poisoned by this chemical). If exposure stops, plasma levels return to normal in 1-2 weeks while red blood cell levels may be reduced for 1-3 months. ⁶ When cholinesterase enzyme levels are reduced by 25% or more below pre-employment levels, risk of poisoning is increased, even if results are in lower ranges of "normal." Reassignment to work not involving *Organophosphate* or *Carbamate* pesticides is recommended until enzyme levels recover.

If symptoms develop or overexposure occurs, repeat the preceding tests as soon as possible and get an exam of the nervous system.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under OSHA 1910.1020.

Mixed Exposures

- * Because smoking can cause heart disease, as well as lung cancer, emphysema, and other respiratory problems, it may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.
- * Persons exposed to other chemicals which affect body cholinesterase (Organophosphates, Carbamates) may be at increased risk.

WORKPLACE CONTROLS AND PRACTICES

Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

In evaluating the controls present in your workplace, consider: (1) how hazardous the substance is, (2) how much of the substance is released into the workplace and (3) whether harmful skin or eye contact could occur. Special controls should be in place for highly toxic chemicals or when significant skin, eye, or breathing exposures are possible.

In addition, the following control is recommended:

* Where possible, automatically transfer solid **TEPP** or pump liquid **TEPP** from drums or other storage containers to process containers.

Good **WORK PRACTICES** can help to reduce hazardous exposures. The following work practices are recommended:

- * Workers whose clothing has been contaminated by **TEPP** should change into clean clothing promptly.
- * Do not take contaminated work clothes home. Family members could be exposed.
- * Contaminated work clothes should be laundered by individuals who have been informed of the hazards of exposure to **TEPP**.
- * Eye wash fountains should be provided in the immediate work area for emergency use.
- * If there is the possibility of skin exposure, emergency shower facilities should be provided.
- * On skin contact with **TEPP**, immediately wash or shower to remove the chemical. At the end of the workshift, wash any areas of the body that may have contacted **TEPP**, whether or not known skin contact has occurred.
- * Do not eat, smoke, or drink where **TEPP** is handled, processed, or stored, since the chemical can be swallowed. Wash hands carefully before eating, drinking, smoking, or using the toilet.
- * For solid **TEPP**, use a vacuum or a wet method to reduce dust during clean-up. DO NOT DRY SWEEP.

PERSONAL PROTECTIVE EQUIPMENT

WORKPLACE CONTROLS ARE BETTER THAN PERSONAL PROTECTIVE EQUIPMENT. However, for some jobs (such as outside work, confined space entry, jobs done only once in a while, or jobs done while workplace controls are being installed), personal protective equipment may be appropriate.

OSHA 1910.132 requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Clothing

- * Avoid skin contact with **TEPP**. Wear protective gloves and clothing. Safety equipment suppliers/manufacturers can provide recommendations on the most protective glove/clothing material for your operation.
- * All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- * Wear impact resistant eye protection with side shields or goggles.
- * Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- * Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.

* Contact lenses should not be worn when working with this substance.

Respiratory Protection

IMPROPER USE OF RESPIRATORS IS DANGEROUS.

Such equipment should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing and medical exams, as described in OSHA 1910.134.

- * For field applications check with your supervisor and your safety equipment supplier regarding the appropriate respiratory equipment.
- * Where the potential exists for exposure over **0.05 mg/m³**, use a MSHA/NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positivepressure mode.
- * Exposure to 5 mg/m³ is immediately dangerous to life and health. If the possibility of exposure above 5 mg/m³ exists, use a MSHA/NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode.

QUESTIONS AND ANSWERS

- Q: If I have acute health effects, will I later get chronic health effects?
- A: Not always. Most chronic (long-term) effects result from repeated exposures to a chemical.
- Q: Can I get long-term effects without ever having short-term effects?
- A: Yes, because long-term effects can occur from repeated exposures to a chemical at levels not high enough to make you immediately sick.
- Q: What are my chances of getting sick when I have been exposed to chemicals?
- A: The likelihood of becoming sick from chemicals is increased as the amount of exposure increases. This is determined by the length of time and the amount of material to which someone is exposed.
- Q: When are higher exposures more likely?
- A: Conditions which increase risk of exposure include <u>dust</u> releasing operations (grinding, mixing, blasting, dumping, etc.), <u>other physical and mechanical processes</u> (heating, pouring, spraying, spills and evaporation from large surface areas such as open containers), and <u>"confined space" exposures</u> (working inside vats, reactors, boilers, small rooms, etc.).

- Q: Is the risk of getting sick higher for workers than for community residents?
- A: Yes. Exposures in the community, except possibly in cases of fires or spills, are usually much lower than those found in the workplace. However, people in the community may be exposed to contaminated water as well as to chemicals in the air over long periods. This may be a problem for children or people who are already ill.

The following information is available from:

New Jersey Department of Health and Senior Services Occupational Health Service PO Box 360 Trenton, NJ 08625-0360 (609) 984-1863 (609) 292-5677 (fax)

Web address: http://www.state.nj.us/health/eoh/odisweb/

Industrial Hygiene Information

Industrial hygienists are available to answer your questions regarding the control of chemical exposures using exhaust ventilation, special work practices, good housekeeping, good hygiene practices, and personal protective equipment including respirators. In addition, they can help to interpret the results of industrial hygiene survey data.

Medical Evaluation

If you think you are becoming sick because of exposure to chemicals at your workplace, you may call personnel at the Department of Health and Senior Services, Occupational Health Service, who can help you find the information you need.

Public Presentations

Presentations and educational programs on occupational health or the Right to Know Act can be organized for labor unions, trade associations and other groups.

<u>Right to Know Information Resources</u>

The Right to Know Infoline (609) 984-2202 can answer questions about the identity and potential health effects of chemicals, list of educational materials in occupational health, references used to prepare the Fact Sheets, preparation of the Right to Know survey, education and training programs, labeling requirements, and general information regarding the Right to Know Act. Violations of the law should be reported to (609) 984-2202.

page 5 of 6

DEFINITIONS

ACGIH is the American Conference of Governmental Industrial Hygienists. It recommends upper limits (called TLVs) for exposure to workplace chemicals.

A carcinogen is a substance that causes cancer.

The **CAS number** is assigned by the Chemical Abstracts Service to identify a specific chemical.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes irreversible damage to human tissue or containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

HHAG is the Human Health Assessment Group of the federal EPA.

IARC is the International Agency for Research on Cancer, a scientific group that classifies chemicals according to their cancer-causing potential.

A **miscible** substance is a liquid or gas that will evenly dissolve in another.

 mg/m^3 means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

MSHA is the Mine Safety and Health Administration, the federal agency that regulates mining. It also evaluates and approves respirators.

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NAERG is the North American Emergency Response Guidebook. It was jointly developed by Transport Canada, the United States Department of Transportation and the Secretariat of Communications and Transportation of Mexico. It is a guide for first responders to quickly identify the specific or generic hazards of material involved in a transportation incident, and to protect themselves and the general public during the initial response phase of the incident.

NCI is the National Cancer Institute, a federal agency that determines the cancer-causing potential of chemicals.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the Public Employees Occupational Safety and Health Act, a state law which sets PELs for New Jersey public employees.

PIH is a DOT designation for chemicals which are Poison Inhalation Hazards.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

TLV is the Threshold Limit Value, the workplace exposure limit recommended by ACGIH.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name:	TEPP
DOT Number:	NA 2783 (Solid)
	NA 3018 (Liquid)
NAERG Code:	152
CAS Number:	107-49-3

Hazard rating	NJDHSS	NFPA		
FLAMMABILITY	Not Found	Not Rated		
REACTIVITY	Not Found	Not Rated		
POISONOUS GASES ARE PRODUCED IN FIRE				
CONTAINERS MAY EXPLODE IN FIRE				

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

FIRE HAZARDS

- * **TEPP** may burn, but does not readily ignite.
- * Use dry chemical, CO₂, water spray, or foam extinguishers.
- * POISONOUS GASES ARE PRODUCED IN FIRE, including highly toxic vapors of unburned material and phosphoric acid.
- * CONTAINERS MAY EXPLODE IN FIRE.
- * Use water spray to keep fire-exposed containers cool.
- * If employees are expected to fight fires, they must be trained and equipped as stated in OSHA 1910.156.

SPILLS AND EMERGENCIES

If liquid **TEPP** is spilled or leaked, or solid **TEPP** is spilled, take the following steps:

- * Evacuate persons not wearing protective equipment from area of spill or leak until clean-up is complete.
- * Remove all ignition sources.
- * Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.
- * Collect powdered material in the most convenient and safe manner and deposit in sealed containers.
- * Ventilate and wash area after clean-up is complete.
- * It may be necessary to contain and dispose of **TEPP** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.
- * If employees are required to clean-up spills, they must be properly trained and equipped. OSHA 1910.120(q) may be applicable.

FOR LARGE SPILLS AND FIRES immediately call your fire department. You can request emergency information from the following:

CHEMTREC: (800) 424-9300 NJDEP HOTLINE: 1-877-WARN-DEP

HANDLING AND STORAGE

- * Prior to working with **TEPP** you should be trained on its proper handling and storage.
- * **TEPP** is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE) and STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE).
- * Store in tightly closed containers in a cool, well-ventilated area away from WATER.

FIRST AID

In NJ, for POISON INFORMATION call 1-800-764-7661

Eye Contact

* Immediately flush with large amounts of water. Continue without stopping for at least 30 minutes, occasionally lifting upper and lower lids. Seek medical attention immediately.

Skin Contact

- * Quickly remove contaminated clothing. Immediately wash area with large amounts of soap and water. Seek medical attention immediately.
- * Shampoo hair promptly if contaminated.

Breathing

- * Remove the person from exposure.
- * Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- * Transfer promptly to a medical facility.
- * Medical observation is recommended for 24 to 48 hours after breathing overexposure, as pulmonary edema may be delayed.

PHYSICAL DATA

Vapor Pressure: 0.0002 mm Hg at 68°F (20°C) **Water Solubility:** Miscible

OTHER COMMONLY USED NAMES

Chemical Name:

Diphosphoric Acid, Tetraethyl Ester

Other Names:

Bladan; Vapotone; Tetraethyl Pyrophosphate; Nifos T; Kilmite; Tetron; Killax; Mortopal

Not intended to be copied and sold for commercial purposes.

NEW JERSEY DEPARTMENT OF HEALTH AND

SENIOR SERVICES Right to Know Program PO Box 368, Trenton, NJ 08625-0368 (609) 984-2202