Nullealth Hazardous Substance Fact Sheet

Common Name: **DIMEFOX**

| Synonyms: | Bis(Dimeth | vlamido |)Fluoro | phos | phate: | DMF |
|-----------|------------|---------|---------|------|--------|-----|
| | | | | | | |

Chemical Name: Phosphorodiamidic Fluoride, Tetramethyl-

Date: February 1999 Revision: May 2009

Description and Use

Dimefox is a colorless liquid with a fishy odor. It was used as an insecticide but is no longer produced or registered for use in the United States.

Reasons for Citation

Dimefox is on the Right to Know Hazardous Substance List because it is cited by DEP and EPA.

SEE GLOSSARY ON PAGE 5.

FIRST AID

Eye Contact

Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while rinsing.

Skin Contact

- Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water. Seek medical attention immediately.
- ► Shampoo hair immediately if contaminated.

Inhalation

- ▶ Remove the person from exposure.
- Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222 CHEMTREC: 1-800-424-9300 NJDEP Hotline: 1-877-927-6337 National Response Center: 1-800-424-8802

| CAS Number: | 115-26-4 |
|-----------------------|----------|
| RTK Substance Number: | 2342 |
| DOT Number: | None |

EMERGENCY RESPONDERS >>>> SEE LAST PAGE

| Hazard Summary | | | |
|--|-------|------|--|
| Hazard Rating | NJDOH | NFPA | |
| HEALTH | 3 | - | |
| FLAMMABILITY | 1 | - | |
| REACTIVITY | 0 | - | |
| POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE | | | |

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- Dimefox can affect you when inhaled and by passing through the skin.
- Exposure can cause rapid, severe Organophosphate poisoning with headache, sweating, nausea and vomiting, diarrhea, loss of coordination, and death.
- ► Inhaling **Dimefox** can irritate the nose, throat and lungs.
- Exposure can cause headache, dizziness, lightheadedness, and passing out.
- Repeated exposure may cause personality changes, such as depression, anxiety or irritability.

Workplace Exposure Limits

No occupational exposure limits have been established for **Dimefox**. However, it may pose a health risk. Always follow safe work practices.

► It should be recognized that **Dimefox** can be absorbed through your skin, thereby increasing your exposure.

Determining Your Exposure

- Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Dimefox**:

- Exposure can cause rapid, severe Organophosphate poisoning with headache, sweating, nausea and vomiting, diarrhea, loss of coordination, and death.
- Inhaling Dimefox can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Dimefox** and can last for months or years:

Cancer Hazard

► According to the information presently available to the New Jersey Department of Health, **Dimefox** has not been tested for its ability to cause cancer in animals.

Reproductive Hazard

► According to the information presently available to the New Jersey Department of Health, **Dimefox** has not been tested for its ability to affect reproduction.

Other Effects

- Exposure can cause headache, dizziness, lightheadedness, and passing out. Lower exposure can affect concentration, memory and vision. Higher levels can cause coma and death.
- Repeated exposure may cause personality changes, such as depression, anxiety or irritability.

Medical

Medical Testing

Before employment and at regular times after that, the following are recommended:

- Plasma and red blood cell cholinesterase levels (tests for the enzyme poisoned by this chemical). If exposure stops, plasma levels return to normal in 1-2 weeks, but red blood cell levels may be reduced for 1-3 months.
- When cholinesterase enzyme levels are reduced by 25% or more below pre-employment levels, risk of poisoning is increased, even if results are in lower ranges of "normal." Reassignment to work not involving Organophosphate or Carbamate pesticides is recommended until enzyme levels recover.

If symptoms develop or overexposure occurs, repeat the preceding tests as soon as possible and get an exam of the nervous system.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

You may be at higher risk if you are exposed to other chemicals that affect cholinesterase levels in the body (Organophosphates and Carbamates).

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at <u>www.cdc.gov/niosh/topics/ctrlbanding/</u>.

The following work practices are also recommended:

- ► Label process containers.
- ▶ Provide employees with hazard information and training.
- Monitor airborne chemical concentrations.
- Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- Wash or shower if skin comes in contact with a hazardous material.
- Always wash at the end of the workshift.
- Change into clean clothing if clothing becomes contaminated.
- ► Do not take contaminated clothing home.
- Get special training to wash contaminated clothing.
- Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- Avoid skin contact with **Dimefox**. Wear personal protective equipment made from material that can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- Safety equipment manufacturers recommend Neoprene and Silver Shield®/4H® as glove materials for Organophosphorus compounds, and Tychem® BR, LV, Responder® and TK, or the equivalent, as protective clothing materials for Organo-phosphorus compounds.
- All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.
- ► Do not wear leather shoes. **Dimefox** is absorbed into the leather and can not be removed by cleaning.

Eye Protection

- ► Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- If additional protection is needed for the entire face, use in combination with a face shield. A face shield should not be used without another type of eye protection.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- At any detectable concentration, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressuredemand or other positive-pressure mode.
- Exposure to 1 mg/m³ is immediately dangerous to life and health. If the possibility of exposure above 1 mg/m³ exists, use a NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode equipped with an emergency escape air cylinder.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ Dimefox may burn, but does not readily ignite.
- ► Use dry chemical, CO₂ or water spray as extinguishing agents.
- POISONOUS GASES ARE PRODUCED IN FIRE, including Phosphine.
- ► CONTAINERS MAY EXPLODE IN FIRE.
- ▶ Use water spray to keep fire-exposed containers cool.

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Dimefox** is spilled or leaked, take the following steps:

- Evacuate personnel and secure and control entrance to the area.
- Eliminate all ignition sources.
- Absorb liquids in vermiculite, dry sand, earth, or a similar material and place into sealed containers for disposal.
- Ventilate area of spill or leak.
- ► DO NOT wash into sewer.
- It may be necessary to contain and dispose of **Dimefox** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Dimefox** you should be trained on its proper handling and storage.

- Dimefox can form highly toxic and flammable Phosphine gas in the presence of REDUCING AGENTS (such as LITHIUM, SODIUM, ALUMINUM and their HYDRIDES).
- ► Dimefox is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE).
- Store in tightly closed containers in a cool, well-ventilated area.
- **Dimefox** is corrosive to METALS.
- Sources of ignition, such as smoking and open flames, are prohibited where **Dimefox** is used, handled, or stored in a manner that could create a potential fire or explosion hazard.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health Right to Know PO Box 368 Trenton, NJ 08625-0368 Phone: 609-984-2202 Fax: 609-984-7407 E-mail: rtk@doh.state.nj.us Web address: http://www.nj.gov/health/eoh/rtkweb

The Right to Know Hazardous Substance Fact Sheets are not intended to be copied and sold for commercial purposes.

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGLs) are established by the EPA. They describe the risk to humans resulting from once-in-a lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A carcinogen is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A combustible substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A fetus is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database on human health effects that may result from exposure to various chemicals, maintained by federal EPA.

LEL or **Lower Explosive Limit**, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

Protective Action Criteria (PAC) are values established by the Department of Energy and are based on AEGLs and ERPGs. They are used for emergency planning of chemical release events.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or **Upper Explosive Limit** is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a force exerted by the vapor in equilibrium with the solid or liquid phase of the same substance. The higher the vapor pressure the higher concentration of the substance in air.



Common Name: DIMEFOX

Synonyms: Bis(Dimethylamido)Fluorophosphate; DMF CAS No: 115-26-4 Molecular Formula: $C_4H_{12}FN_2OP$ RTK Substance No: 2342 Description: Colorless liquid with a fishy odor

| Hazard Rating | Firefighting | Reactivity | |
|------------------------------|---|--|--|
| 3 - Health 1 - Fire | Dimefox may burn, but does not readily ignite. Use dry chemical, CO_2 or water spray as | Dimefox can form highly toxic and flammable <i>Phosphine</i> gas in the presence of REDUCING AGENTS (such as LITHIUM, SODIUM, ALUMINUM and their HYDRIDES). | |
| 0 - Reactivity DOT#: None | extinguishing agents. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Phosphine</i> . | Dimefox is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, | |
| ERG Guide #: 152 | CONTAINERS MAY EXPLODE IN FIRE. Use water spray to keep fire-exposed containers | PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE). Dimefox is corrosive to METALS. | |
| Hazard Class: 6.1 (Toxic) | cool. | | |

SPILL/LEAKS

Isolation Distance:

Spill: 50 meters (150 feet)

Fire: 800 meters (1/2 mile)

Absorb liquids in vermiculite, dry sand, earth, or a similar material and place into sealed containers for disposal.

DO NOT wash into sewer.

Dimefox may pollute waterways.

EXPOSURE LIMITS

IDLH: 1 mg/m³

The Protective Action Criteria values are:

No information

 $PAC-1 = 0.6 \text{ mg/m}^3$

 $PAC-2 = 1 \text{ mg/m}^3$

 $PAC-3 = 1 \text{ mg/m}^3$

| | | OTO |
|-----|------|-----|
| HEA | EFFE | CIS |
| | | |

Eyes:

Skin: No information

Inhalation: Nose, throat and lung irritation with coughing, wheezing and shortness of breath Headache, sweating, nausea and vomiting, loss of coordination, and death

(Organophosphate poisoning)

PHYSICAL PROPERTIES

| Odor Threshold: | Fishy odor |
|-----------------------|---------------------------|
| Flash Point: | May burn |
| Vapor Pressure: | 0.36 mm Hg at 77°F (25°C) |
| Specific Gravity: | 1.1 (water = 1) |
| Water Solubility: | Soluble |
| Boiling Point: | 187°F (86°C) |
| Molecular Weight: | 154.1 |
| | |

PROTECTIVE EQUIPMENT

Gloves: Neoprene and Silver Shield®/4H® (>8-hr breakthrough for Organo-phosphorus compounds)

Coveralls: Tychem® BR, LV, Responder® and TK (>8-hr breakthrough for *Organo-phosphorus compounds*)

Respirator: SCBA

FIRST AID AND DECONTAMINATION

Remove the person from exposure.

- **Flush** eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn.
- **Quickly** remove contaminated clothing and wash contaminated skin with large amounts of water. Seek medical attention immediately.
- Shampoo hair immediately if contaminated.
- **Begin** artificial respiration if breathing has stopped and CPR if necessary. **Transfer** promptly to a medical facility.