


pen table=\\\\jddpgr\\wa\\system\\jddoteng\\plot\\tbla\\roadway\\Detail\_13x17.tbl  
scale=61734946:1000000  
date=05-APR-2022 08:43  
ID= 000754207



25 35 40 MPH KEEP BUS ONLY BIKE LANE

AREA=17.6 S.F. AREA=17.9 S.F. AREA=19.5 S.F. AREA = 20 S.F. AREA = 24 S.F. AREA = 20 S.F. AREA = 22 S.F. AREA = 21 S.F. AREA = 24 S.F.

YIELD SLOW SCHOOL AHEAD TURN XING PED NO

AREA = 24 S.F. AREA = 23 S.F. AREA = 35 S.F. AREA = 31 S.F. AREA = 24 S.F. AREA = 21 S.F. AREA = 18 S.F. AREA = 14 S.F.

SIGNAL LEFT RIGHT STOP TO OR DO NOT BLOCK

AREA = 32 S.F. AREA = 19 S.F. AREA = 26 S.F. AREA = 22 S.F. AREA = 14 S.F. AREA = 14 S.F. AREA = 14 S.F. AREA = 18 S.F. AREA = 30 S.F.

NORTH SOUTH WEST EAST

AREA = 31 S.F. AREA = 29 S.F. AREA = 24 S.F. AREA = 22 S.F.

NOTES:

1. All number and letter pavement markings are white in color.
2. The space between words should be at least four times the height of the characters for low speed roads, but not more than ten times the height of the characters. The space may be reduced appropriately where there is limited space because of local conditions.
3. If a message consists of more than one word, it should read "UP", i.e., the first word should be nearest the driver.
4. Minor variations in dimensions may be accepted by the Resident Engineer.
5. Portions of a letter, number or symbol may be separated by connecting segments not to exceed 2" in width.
6. Word and Symbol marking should not exceed three lines of information.
7. All Word markings are 8' in height.

TRAFFIC MARKING SYMBOLS

N.T.S. CD-610-13

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

CD-610-13.1