

















NOTES:

1. SEE CD-609-13 FOR ADDITIONAL NOTES AND DETAILS.
2. THE MINIMUM TAPER LENGTH IS BASED ON PARAPET HEIGHT. THE TAPER MUST BE 5:1 OR FLATTER WITH 8:1 DESIRABLE. SEE BRIDGE PLANS FOR TAPER LENGTH.
3. REINFORCEMENT STEEL IS IN METRIC UNITS.
4. FOR ADDITIONAL PARAPET DETAILS & DIMENSIONS, REFER TO BCD-509-6.

GUIDE RAIL ATTACHMENT – NEW CONSTRUCTION – DESIGN SPEED GREATER THAN 45 MPH (MASH TL–3)
SIDEWALK WITH ONE RAIL STEEL BRIDGE RAILING PARAPET

BEAM GUIDE RAIL ATTACHMENTS

N.T.S.

CD-609-16

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

CD-609-16.1

77
164

BDC17D-02-REVISIONS TO CD-609-16
BDC16D-01-ORIGINAL SHEET

ID= TT2VTLL date= 19-JUL-2017 14:36 scale= 63.989071:1.000000 pen table= \\NJDOTPRJWS\Vdgystem\NJDOTWS\Projects\NJDOTBasg\plot\TBLs\Roadway\Details_11x17.tbl
file=