

15" x VARIABLE HEIGHT CONCRETE BARRIER CURB, DOWELLED



15" x 41" CONCRETE BARRIER CURB

NOTES:

1. SEE GENERAL NOTES APPLYING TO ALL BARRIER CURB CD-607-3.2.
2. COMPACT ACCORDING TO SUBSECTION 202.03.
3. SHAPE AND COMPACT THE FILL BETWEEN THE CURBS TO A FIRM EVEN SURFACE. REMOVE UNSUITABLE MATERIAL AND REPLACE WITH ACCEPTABLE MATERIAL AND COMPACT.

CD-607-2.1



CURB TREATMENT AT BERM SECTION AND ALL CURB ENDS

CD-607-2.2



APPROACH CURBED GORE AREA TREATMENT

CD-607-2.3



CURB SIZE	DIM. A	DIM. B	DIM. C	DIM. D
9" x 16"	16"	4"	14"	2"
9" x 18"	18"	6"	16"	4"

METHOD OF DEPRESSING CURB AT DRIVEWAYS

CD-607-2.4



LINEAR CURB TRANSITION

CD-607-2.5

NOTE:
REINFORCEMENT STEEL IS IN METRIC UNITS
HMA = HOT MIX ASPHALT

BARRIER CURB AND VERTICAL CURB

N.T.S.

CD-607-2

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

ID=TP2VILL date=28-SEP-2016 11:08 scale=63.073306:1.000000 pen table= \\NJDOTRSWS\Projects\NJDOTEsig\plot\TELe\Roadway\Details_11x17.tbl
BDCMD-01-ORIGINAL SHEET
file=