


pen table=\\NDOT\PRJ\W\Vegetation\NDOT\Eng\Project\TBA\Roadway\Detail\13c17.tbl

scale=63.073306:1.000000


date=28-SEP-2016 11:10

ID=TP2VLL




BDC:RD-01-ORIGINAL SHEET




SHOULDER RUMBLE STRIP AT ACCELERATION LANE




SHOULDER RUMBLE STRIP AT DECELERATION LANE



SHOULDER RUMBLE STRIP PLACEMENT



COMBINED CENTERLINE RUMBLE STRIP AND APPURTENANCES



CENTERLINE RUMBLE STRIP PLACEMENT

GENERAL NOTES:

1. THE MINIMUM LENGTH OF RUMBLE STRIPS MEASURED LONGITUDINALLY ALONG THE SHOULDER OR CENTERLINE IS 100 FEET.
2. SHOULDER RUMBLE STRIPS TO BE CONSTRUCTED ON 3 FEET OR WIDER INSIDE SHOULDERS, AND 6 FEET OR WIDER OUTSIDE SHOULDERS.
3. THE MINIMUM ADJACENT LANE WIDTH FOR CENTERLINE RUMBLE STRIPS IS 10 FEET.
4. DO NOT CONSTRUCT RUMBLE STRIPS ON BRIDGE DECKS.
5. DO NOT CONSTRUCT SHOULDER RUMBLE STRIPS WITHIN 100 FEET BEFORE AND 100 FEET AFTER THE P.C. OF INTERSECTING ROADWAYS AND COMMERCIAL DRIVEWAYS.
6. CONSTRUCT CENTERLINE RUMBLE STRIPS TO THE END OF THE CENTERLINE STRIPE AT ALL STREET INTERSECTIONS. CENTERLINE RUMBLE STRIPS TO BE CONTINUOUS AND NOT BREAK AT DRIVEWAYS.
7. DO NOT CONSTRUCT CENTERLINE RUMBLE STRIPS ALONG LEFT TURN SLOTS AND CONTINUOUS TWO WAY LEFT TURN MEDIAN LANES.
8. APPURTENANCES INCLUDE, BUT ARE NOT LIMITED TO, RAISED PAVEMENT MARKERS, MANHOLES, INLETS, VALVE BOXES, AND MONUMENT BOXES.
9. DO NOT CONSTRUCT RUMBLE STRIPS 200 FEET BEFORE AND AFTER THE APPROXIMATE MIDPOINT OF WEIGH-IN-MOTION (WIM) SYSTEMS IN THE ROADWAY.

NOTE:
HMA = HOT MIX ASPHALT

RUMBLE STRIPS

N.T.S.

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS

CD-610-5.1