



pen table=\\NDOT\RTW\Wegway\CD-608-1.000000 date=28-SEP-2016 11:08 ID=TP2VLL




PLAN VIEW




SECTION VIEW

NON-VEGETATIVE SURFACES AROUND GUIDE RAIL BEHIND CURB OR RAISED BERM

CD-608-1.1




PLAN VIEW




SECTION VIEW

NON-VEGETATIVE SURFACE AT EDGE OF PAVEMENT ON UMBRELLA SECTION WHERE GUIDE RAIL IS USED

CD-608-1.2




PLAN VIEW




SECTION VIEW

NON-VEGETATIVE SURFACES AROUND GUIDE RAIL ANCHORAGE

CD-608-1.3




PLAN VIEW



SECTION VIEW

LEAVE OUT FOR NON-VEGETATIVE SURFACE, HOT MIX ASPHALT ONLY


CD-608-1.4



PLAN VIEW

NON-VEGETATIVE SURFACE AROUND FLARED GUIDE RAIL WHERE GUIDE RAIL OFFSET FROM EDGE OF PAVEMENT IS GREATER THAN 4'-0"


CD-608-1.5



PLAN VIEW

NON-VEGETATIVE SURFACE AROUND FLARED GUIDE RAIL WHERE GUIDE RAIL OFFSET FROM EDGE OF PAVEMENT IS 4'-0" OR LESS

CD-608-1.6



SECTION VIEW

TOPSOILING 4" THICK, FERTILIZING & SEEDING STRAW MULCHING Z = 3' FOR GUIDE RAIL, DUAL FACED 4' FOR MODIFIED THRIE BEAM, DUAL FACED TOPSOILING 4" THICK, FERTILIZING & SEEDING STRAW MULCHING


NOTE:
WHERE X IS LESS THAN OR EQUAL TO 4', USE Y TO DETERMINE NON-VEGETATIVE SURFACE TREATMENT FOR THAT SIDE OF GUIDE RAIL.

NON-VEGETATIVE SURFACE, UNDER MEDIAN GUIDE RAIL

CD-608-1.7

| X | Y |
|---|--|
| GUIDE RAIL OFFSET FROM EDGE OF PAVEMENT | WIDTH OF NON-VEGETATIVE SURFACE IN FRONT OF GUIDE RAIL |
| 7'-0" OR GREATER | 2'-0" |
| 4'-0" | 4'-0" |
| 0'-0" | 0'-0" |

CD-608-1.8




PLAN VIEW

NON-VEGETATIVE SURFACE AROUND OVERHEAD SIGN FOUNDATIONS AND UNDER LARGE GROUND MOUNTED SIGNS

CD-608-1.9

- GENERAL NOTES:**
- IF THE END OF THE GUIDE RAIL IS BURIED IN THE SLOPE, THE LIMIT OF NON-VEGETATIVE SURFACE RELATIVE TO THE BURIED GUIDE RAIL WILL BE DETERMINED BY THE RE.
 - SEE TYPICAL SECTIONS FOR CROSS SLOPES IN ROADSIDE (BORDER OR SIDEWALK AREA).
 - LEAVE OUTS CAN BE FILLED WITH:
1. COURSE AGREGATE, SIZE NO. 57 TO BE HAND TAMPED, THEN SEAL SURFACE WITH EMULSIFIED ASPHALT AT 0.35 GAL/SY ±0.05 AS PER STANDARD SPECIFICATIONS SECTION 902; OR
2. COURSE AGREGATE, SIZE NO. 57 IN BASE OF LEAVE OUT AND TOP WITH NON-VEGETATIVE SURFACE, HMA, 2" THICK. GRADE TO DRAIN AND HAND TAMP LEAVE OUT SURFACE.

CD-608-1.10



PLAN VIEW

NON-VEGETATIVE SURFACE AT MEDIAN GUIDE RAIL

CD-608-1.11

NON-VEGETATIVE SURFACE N.T.S.

CD-608-1

NEW JERSEY DEPARTMENT OF TRANSPORTATION

CONSTRUCTION DETAILS