


**New Jersey Department of Transportation**

1035 Parkway Avenue, PO Box 600, Trenton, New Jersey 08625-0600

**Baseline Document Change Announcement**



**Joint Sealers**

**BDC04S-07**

**June 04, 2004**

**SUBJECT: Revision to Subsection 908.02 to the 2001 Standard Specifications in English and Metric units related to Joint Sealers**

Subsection 908.02 has been revised to adopt the new ASTM specifications developed to implement the results of the successful research done under the State Highway Research Program (SHRP).

The following revisions have been incorporated in both the English unit Standard Input *SI2001E1* and Metric unit Standard Input *SI2001M1* as of June 04, 2004.

**908.02 Joint Sealers.**

THE FIRST PARAGRAPH IS CHANGED TO:

Hot-poured joint sealer for joints and cracks in both HMA and portland cement concrete surface course shall be sealant conforming to Subsections 908.06, 908.07, and ASTM D 6690 as follows:

1. Type II Sealant shall be used when sealing cracks in HMA.
2. Type IV Sealant shall be used when sealing joints and cracks in Portland cement concrete pavements and HMA saw and seal applications.

**Implementation Code R (ROUTINE)**

Changes must be implemented in all applicable Department projects scheduled for Final Design Submission at least one month after the date of the BDC announcement. This will allow designers to make necessary plan, specifications, and estimate/proposal changes without requiring the need for an addenda or postponement of advertisement or receipt of bids.

**Recommended By:**

**Approved By:**

ORIGINAL SIGNED

ORIGINAL SIGNED

---

Brian Strizki  
Director,  
Quality Management Services

---

F. Howard Zahn  
Assistant Commissioner,  
Capital Program Management