



Right to Know Hazardous Substance Fact Sheet

Common Name: **BROMINE**

Synonyms: None

Chemical Name: Bromine

Date: November 2007 Revision: April 2017

Description and Use

Bromine is a corrosive dark, reddish-brown, fuming liquid or vapor. It is used as an additive in gasoline, in making fire retardants, dyes, pharmaceuticals, fumigants and photographic chemicals, and in water purification.

► ODOR THRESHOLD=0.051 to 3.5 ppm

- Odor thresholds vary greatly. Do not rely on odor alone to determine potentially hazardous exposures.

Reasons for Citation

- Bromine** is on the Right to Know Hazardous Substance List because it is cited by OSHA, ACGIH, DOT, NIOSH, DEP, NFPA and EPA.
- This chemical is on the Special Health Hazard Substance List.

[SEE GLOSSARY ON PAGE 5.](#)

FIRST AID

Eye Contact

- Immediately flush with large amounts of water for at least 30 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention immediately.

Skin Contact

- Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water. Seek medical attention immediately.

Inhalation

- Remove the person from exposure.
- Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- Transfer promptly to a medical facility.
- Medical observation is recommended for 24 to 48 hours after overexposure, as pulmonary edema may be delayed.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

CAS Number: 7726-95-6

RTK Substance Number: 0252

DOT Number: UN 1744

EMERGENCY RESPONDERS >>> SEE BACK PAGE

Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	-	3
FLAMMABILITY	-	0
REACTIVITY	-	0
CORROSIVE STRONG OXIDIZER POISONOUS GASES ARE PRODUCED IN FIRE		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious;
4=severe

- Bromine** can affect you when inhaled and by passing through the skin.
- Contact can severely irritate and burn the skin and eyes.
- Inhaling **Bromine** can irritate the nose and throat.
- Inhaling **Bromine** can irritate the lungs. Higher exposures may cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency.
- Repeated exposure can cause headache, dizziness, nausea and vomiting.
- Bromine** is not combustible but it is a STRONG OXIDIZER which enhances the combustion of other substances.

Workplace Exposure Limits

OSHA: The legal airborne permissible exposure limit (PEL) is **0.1 ppm** averaged over an 8-hour workshift.

NIOSH: The recommended airborne exposure limit (REL) is **0.1 ppm** averaged over a 10-hour workshift and **0.3 ppm**, not to be exceeded during any 15-minute work period.

ACGIH: The threshold limit value (TLV) is **0.1 ppm** averaged over an 8-hour workshift and **0.2 ppm** as a STEL (short-term exposure limit).

- The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health and Senior Services Hazardous Substance Fact Sheet, available on the RTK Program website (<http://nj.gov/health/workplacehealthandsafety/right-to-know/>) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) requires private employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Bromine**:

- ▶ Contact can severely irritate and burn the eyes causing watery eyes, redness and pain.
- ▶ Contact can irritate the skin and cause severe burns, discoloration and slow healing ulcers.
- ▶ Inhaling **Bromine** can irritate the nose and throat.
- ▶ Inhaling **Bromine** can irritate the lungs causing coughing and/or shortness of breath. Higher exposures may cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency, with severe shortness of breath.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Bromine** and can last for months or years:

Cancer Hazard

- ▶ According to the information presently available to the New Jersey Department of Health, **Bromine** has not been tested for its ability to cause cancer in animals.

Reproductive Hazard

- ▶ There is limited evidence that **Bromine** may damage the male reproductive system (including decreasing the sperm count and affect fertility).

Other Effects

- ▶ Repeated exposure can cause headache, dizziness, nausea and vomiting.
- ▶ **Bromine** can irritate the lungs. Repeated exposure may cause bronchitis to develop with coughing, phlegm, and/or shortness of breath.

Medical

Medical Testing

For frequent or potentially high exposure (half the PEL or greater), the following are recommended before beginning work and at regular times after that:

- ▶ Lung function tests

If symptoms develop or overexposure is suspected, the following is recommended:

- ▶ Consider chest x-ray after acute overexposure

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- ▶ Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Bromine**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend *Neoprene* and *Nitrile* for gloves and DuPont *Tychem® TK* (40 min. breakthrough sat. vapor; >8-hr breakthrough @ 10 g/m²) as protective material for clothing.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear non-vented, impact resistant goggles when working with fumes, gases, or vapors.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- ▶ Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ Where the potential exists for exposure over **0.1 ppm**, use a NIOSH approved full facepiece respirator with an organic vapor/acid gas cartridge which is specifically approved for **Bromine**. Increased protection is obtained from full facepiece powered-air purifying respirators.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Bromine**, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.
- ▶ Consider all potential sources of exposure in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- ▶ Where the potential exists for exposure greater than **1 ppm** but less than **3 ppm**, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus or an emergency escape air cylinder.
- ▶ Exposure to **3 ppm** is immediately dangerous to life and health. If the possibility of exposure above **3 ppm** exists, use a NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode equipped with an emergency escape air cylinder.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ **Bromine** is not combustible but it is a **STRONG OXIDIZER** which will enhance the burning of other materials.
- ▶ Extinguish fire using an agent suitable for type of surrounding fire.
- ▶ **POISONOUS GASES ARE PRODUCED IN FIRE.**
- ▶ Use water spray to keep fire-exposed containers cool.
- ▶ **Bromine** may ignite combustible and organic materials (wood, paper and oil).

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Bromine** is spilled or leaked, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Cover with dry lime, sand or soda ash, and place in covered containers for disposal.
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ It may be necessary to contain and dispose of **Bromine** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Bromine** you should be trained on its proper handling and storage.

- ▶ **Bromine** will react violently with ALUMINUM and AQUEOUS AMMONIA.
- ▶ **Bromine** is not compatible with REDUCING AGENTS (such as LITHIUM, SODIUM, and their HYDRIDES); MERCURY; PHOSPHORUS; TITANIUM; POTASSIUM; SODIUM; HALOCARBONS; METAL CARBIDES; METAL SALTS; AMINES; and OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE).
- ▶ Contact with COMBUSTIBLE and ORGANIC MATERIALS (such as FUELS, WOOD and OILS) may cause a fire.
- ▶ **Bromine** will attack METALS (such as IRON, STEEL, STAINLESS STEEL and COPPER).
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from HEAT.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health
Right to Know Program
PO Box 368
Trenton, NJ 08625-0368
Phone: 609-984-2202
Fax: 609-984-7407
E-mail: rtk@doh.nj.gov
Web address:
<http://nj.gov/health/workplacehealthandsafety/right-to-know/>

*The Right to Know Hazardous Substance Fact Sheets
are not intended to be copied and sold
for commercial purposes.*

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGLs) are established by the EPA. They describe the risk to humans resulting from once-in-a lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values are intended to provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database maintained by federal EPA. The database contains information on human health effects that may result from exposure to various chemicals in the environment.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

PIH is a DOT designation for chemicals which are Poison Inhalation Hazards.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name: BROMINE

Synonyms: None

CAS No: 7726-95-6

Molecular Formula: Br₂
RTK Substance No: 0252

Description: Dark, reddish-brown, corrosive, fuming liquid or vapor

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
3 - Health	Bromine is not combustible but it is a STRONG OXIDIZER which will enhance the burning of other materials.	Bromine will react violently with ALUMINUM and AQUEOUS AMMONIA.
0 - Fire	Extinguish fire using an agent suitable for type of surrounding fire.	Bromine is not compatible with REDUCING AGENTS (such as LITHIUM, SODIUM, and their HYDRIDES); MERCURY; PHOSPHORUS; TITANIUM; POTASSIUM; SODIUM; HALOCARBONS; METAL CARBIDES; METAL SALTS; AMINES; and OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE).
0 - Reactivity	POISONOUS GASES ARE PRODUCED IN FIRE	Contact with COMBUSTIBLE and ORGANIC MATERIALS (such as FUELS, WOOD and OILS) may cause a fire.
DOT#: UN 1744	Use water spray to keep fire-exposed containers cool.	Bromine will attack METALS (such as IRON, STEEL, STAINLESS STEEL and COPPER).
ERG Guide #: 154		
Hazard Class: 8 (Corrosive)		

SPILL/LEAKS

Isolation Distance:

Small Spills: 60 meters (200 feet)

Large Spills: 330 meters (1,100 feet)

Cover with dry lime, sand or soda ash, and place in covered containers for disposal.

PHYSICAL PROPERTIES

Odor Threshold:	0.051 - 3.5 ppm
Flash Point:	Not Combustible
Vapor Density:	5.5 (air = 1)
Vapor Pressure:	175 mm Hg at 68°F (20°C)
Specific Gravity:	3.12 (water = 1)
Water Solubility:	Very slightly soluble
Boiling Point:	138°F (58.8°C)
Melting Point:	19.4°F (-7.25°C)
Ionization Potential:	10.55 eV
Molecular Weight:	159.8

EXPOSURE LIMITS

OSHA:	0.1 ppm, 8-hr TWA
NIOSH:	0.1 ppm, 10-hr TWA; 0.3 ppm STEL
ACGIH:	0.1 ppm, 8-hr TWA; 0.2 ppm STEL
IDLH LEVEL:	3 ppm
PAC LEVELS:	PAC-1 = 0.033 ppm; PAC-2 = 0.24 ppm; PAC-3 = 8.5 ppm

HEALTH EFFECTS

Eyes:	Irritation, burns
Skin:	Irritation, burns, discoloration and slowly healing ulcers
Acute:	Irritation of nose, throat and lungs with coughing and shortness of breath
Chronic:	Coughing, phlegm and shortness of breath, headache, dizziness

PROTECTIVE EQUIPMENT

Gloves:	Neoprene and Nitrile (>8-hr breakthrough for <i>Bromine water</i>)
Coveralls:	DuPont Tychem® TK (40 min. breakthrough sat. vapor; >8-hr breakthrough @ 10 g/m ³)
Boots:	Neoprene
Respirator:	> 0.1 ppm - full facepiece APR with OV/AG cartridges > 1 ppm - Pressure demand supplied-air > 3 ppm - Pressure demand SCBA

FIRST AID AND DECONTAMINATION

Remove the person from exposure.
Flush eyes with large amounts of water for at least 30 minutes. Remove contact lenses if worn. Seek medical attention immediately.
Quickly remove contaminated clothing and wash contaminated skin with large amounts of soap and water. Seek medical attention immediately.
Begin artificial respiration if breathing has stopped and CPR if necessary.
Transfer to a medical facility.
Medical observation is recommended as symptoms may be delayed.