



Right to Know Hazardous Substance Fact Sheet

Common Name: **CAPTAN**

Synonyms: Captane; Orthocide; Vanicide

Chemical Name: 1H-Isoindole-1,3(2H)-Dione, 3a,4,7,7a-Tetrahydro-2-[(Trichloromethyl)Thio]-

Date: August 1998 Revision: February 2008

CAS Number: 133-06-2

RTK Substance Number: 0339

DOT Number: UN 3077

Description and Use

Captan is a white, odorless, crystalline solid when pure. The technical grade is a cream to yellow powder with a strong odor. **Captan** is often dissolved in a liquid carrier and is used as a fungicide in paints, plastics, leather and fabrics. It is also used as a fungicide for crops and in seed treatment.

Reasons for Citation

- ▶ **Captan** is on the Right to Know Hazardous Substance List because it is cited by ACGIH, DOT, NIOSH, DEP, IARC, IRIS and EPA.

[SEE GLOSSARY ON PAGE 5.](#)

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while rinsing.

Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE BACK PAGE

Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	2	-
FLAMMABILITY	0	-
REACTIVITY	1	-
POISONOUS GASES ARE PRODUCED IN FIRE		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Captan** can affect you when inhaled and by passing through the skin.
- ▶ Contact can irritate the skin and eyes.
- ▶ Inhaling **Captan** can irritate the nose and throat.
- ▶ Exposure to **Captan** can cause headache, dizziness, nausea and vomiting.
- ▶ **Captan** may cause a skin allergy.
- ▶ *Pure Captan* does not burn, however it is often dissolved in a liquid carrier which may be flammable or combustible.

Workplace Exposure Limits

NIOSH: The recommended airborne exposure limit (REL) is **5 mg/m³** averaged over a 10-hour workshift.

ACGIH: The threshold limit value (TLV) is **5 mg/m³** (as the *inhalable fraction*) averaged over an 8-hour workshift.

- ▶ The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require private employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Captan**:

- ▶ Contact can irritate the skin and eyes.
- ▶ Inhaling **Captan** can irritate the nose and throat.
- ▶ Exposure to **Captan** can cause headache, dizziness, nausea and vomiting.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Captan** and can last for months or years:

Cancer Hazard

- ▶ While **Captan** has been tested, it is not classifiable as to its potential to cause cancer.
- ▶ **Captan** may cause mutations (genetic changes).

Reproductive Hazard

- ▶ There is limited evidence that **Captan** is a teratogen in animals. Until further testing has been done, it should be treated as a possible teratogen in humans.

Other Effects

- ▶ **Captan** may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.

Medical

Medical Testing

If symptoms develop or overexposure is suspected, the following is recommended:

- ▶ Evaluation by a qualified allergist can help diagnose skin allergy.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Captan**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend *Rubber* and *Nitrile* for gloves and DuPont *Tyvek*® as a protective material for *solid Captan*.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear eye protection with side shields or goggles.
- ▶ Wear indirect-vent, impact and splash resistant goggles when working with liquid formulations.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- ▶ Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ For field applications check with your supervisor and your safety equipment supplier regarding the appropriate respiratory equipment.
- ▶ Where the potential exists for exposure over **5 mg/m³**, use a NIOSH approved respirator with an organic vapor cartridge and particulate prefilters. Increased protection is obtained from full facepiece powered-air purifying respirators.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Captan**, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.
- ▶ Consider all potential sources of exposure in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- ▶ Where the potential exists for exposure over **50 mg/m³**, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ *Pure Captan* does not burn, however it is often dissolved in a liquid carrier which may be flammable or combustible.
- ▶ Use dry chemical, CO₂, water spray or foam as extinguishing agents.
- ▶ **POISONOUS GASES ARE PRODUCED IN FIRE**, including *Sulfur Oxides*, *Nitrogen Oxides*, *Hydrogen Chloride* and *Phosgene*.
- ▶ Use water spray to keep fire-exposed containers cool.

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Captan** or **Captan solution** is spilled or leaked, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Moisten spilled material first or use a HEPA-filter vacuum for clean-up.
- ▶ Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ It may be necessary to contain and dispose of **Captan** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Captan** you should be trained on its proper handling and storage.

- ▶ **Captan** is not compatible with STRONG ALKALIES (such as LIME); TETRAETHYL PYROPHOSPHATE; OIL SPRAYS; and PARATHION.
- ▶ **Captan** may react with WATER to form *Hydrogen Chloride gas*.
- ▶ **Captan** is corrosive to METALS in the presence of MOISTURE.
- ▶ Store in tightly closed containers in a cool, well-ventilated area.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health
Right to Know
PO Box 368
Trenton, NJ 08625-0368
Phone: 609-984-2202
Fax: 609-984-7407
E-mail: rtk@doh.state.nj.us
Web address: <http://www.nj.gov/health/eoh/rtkweb>

***The Right to Know Hazardous Substance Fact Sheets
are not intended to be copied and sold
for commercial purposes.***

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGs) are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values are intended to provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database maintained by federal EPA. The database contains information on human health effects that may result from exposure to various chemicals in the environment.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

PIH is a DOT designation for chemicals which are Poison Inhalation Hazards.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name: **CAPTAN**

Synonyms: Captane; Orthocide; Vanicide

CAS No: 133-06-2

 Molecular Formula: $C_9H_8Cl_3NO_2S$

RTK Substance No: 0339

Description: White, odorless, crystalline solid when pure or cream to yellow powder with a strong odor (technical grade)

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
2 - Health 0 - Fire 1 - Reactivity DOT#: UN 3077 ERG Guide #: 171 Hazard Class: 9 (miscellaneous/ hazardous material)	Pure Captan does not burn, however it is often dissolved in a liquid carrier which may be flammable or combustible. Use dry chemical, CO ₂ , water spray or foam as extinguishing agents. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Sulfur Oxides, Nitrogen Oxides, Hydrogen Chloride and Phosgene.</i> Use water spray to keep fire-exposed containers cool.	Captan is not compatible with STRONG ALKALIES (such as LIME); TETRAETHYL PYROPHOSPHATE; OIL SPRAYS; and PARATHION. Captan may react with WATER to form <i>Hydrogen Chloride gas.</i> Captan is corrosive to METALS in the presence of MOISTURE.

SPILL/LEAKS

Isolation Distance:

Spill: 25 meters (75 feet)

Fire: 800 meters (1/2 mile)

Moisten spilled material first or use a HEPA-filter vacuum for clean-up.

Absorb liquids in vermiculite, dry sand, earth, or a similar material and deposit in sealed containers.

May be hazardous to aquatic and soil organisms.

PHYSICAL PROPERTIES

Odor Threshold:	Odorless (when pure)
Vapor Pressure:	0 mm Hg at 68°F (20°C)
Specific Gravity:	1.74 (water = 1)
Water Solubility:	Very slightly soluble
Boiling Point:	Decomposes
Melting Point:	352°F (178°C)
Molecular Weight:	300.6

EXPOSURE LIMITS

NIOSH: 5 mg/m³, 10-hr TWA

ACGIH: 5 mg/m³, 8-hr TWA (as the inhalable fraction)

PROTECTIVE EQUIPMENT

Gloves:	Rubber or Nitrile
Coveralls:	DuPont Tyvek® or equivalent
Respirator:	>5 mg/m ³ - Full facepiece APR with Organic vapor cartridge and High efficiency pre-filters >50 mg/m ³ - Supplied air

HEALTH EFFECTS

Eyes:	Irritation
Skin:	Irritation, skin rash and itching
Inhalation:	Nose and throat irritation Headache, dizziness, nausea and vomiting

FIRST AID AND DECONTAMINATION

Remove	the person from exposure.
Flush	eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn.
Remove	contaminated clothing and wash contaminated skin with large amounts of soap and water.
Transfer	to a medical facility.