



Right to Know Hazardous Substance Fact Sheet

Common Name: **COBALT NAPHTHENATE**

Synonyms: Cobalt Naphtha; Naftolite

Chemical Name: Naphthenic Acids, Cobalt Salts

Date: September 1998 Revision: February 2008

CAS Number: 61789-51-3

RTK Substance Number: 0523

DOT Number: UN 2001

Description and Use

Cobalt Naphthenate is an odorless, brown powder or bluish-red solid. It is often used in a solution of *Mineral Oils* or *Mineral Spirits*. It is used in paint varnish and ink drier, and in bonding rubber to steel and other materials.

Reasons for Citation

- ▶ **Cobalt Naphthenate** is on the Right to Know Hazardous Substance List because it is cited by DOT, DEP, IARC, NFPA and EPA.
- ▶ This chemical is on the Special Health Hazard Substance List.

SEE GLOSSARY ON PAGE 5.

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while rinsing.

Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE BACK PAGE

Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	2	1
FLAMMABILITY	2	2
REACTIVITY	0	0
CARCINOGEN COMBUSTIBLE POISONOUS GASES ARE PRODUCED IN FIRE		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Cobalt Naphthenate** can affect you when inhaled.
- ▶ **Cobalt Naphthenate** should be handled as a CARCINOGEN--WITH EXTREME CAUTION.
- ▶ Contact can irritate the skin and eyes.
- ▶ Inhaling **Cobalt Naphthenate** can irritate the nose, throat and lungs.
- ▶ **Cobalt Naphthenate** may cause a skin allergy.
- ▶ **Cobalt Naphthenate** may cause an asthma-like allergy.
- ▶ Repeated exposure may cause permanent lung scarring.
- ▶ **Cobalt Naphthenate** in *powder* or *granular* form may explode when mixed with air.

Workplace Exposure Limits

No occupational exposure limits have been established for **Cobalt Naphthenate**. However, it may pose a health risk. Always follow safe work practices.

- ▶ **Cobalt Naphthenate** may be a CARCINOGEN in humans. There may be no safe level of exposure to a carcinogen, so all contact should be reduced to the lowest possible level.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Cobalt Naphthenate**:

- ▶ Contact can irritate the skin and eyes.
- ▶ Inhaling **Cobalt Naphthenate** can irritate the nose and throat causing coughing and wheezing.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Cobalt Naphthenate** and can last for months or years:

Cancer Hazard

- ▶ **Cobalt Naphthenate** may be a CARCINOGEN in humans. There is some evidence that *Cobalt* and *Cobalt compounds* cause lung cancer in humans.
- ▶ Many scientists believe there is no safe level of exposure to a carcinogen. Such substance may also have the potential for causing reproductive damage in humans.

Reproductive Hazard

- ▶ According to the information presently available to the New Jersey Department of Health, **Cobalt Naphthenate** has not been tested for its ability to affect reproduction.

Other Effects

- ▶ **Cobalt Naphthenate** may cause a skin allergy. If allergy develops, very low future exposure can cause itching and a skin rash.
- ▶ **Cobalt Naphthenate** may cause an asthma-like allergy. Future exposure can cause asthma attacks with shortness of breath, wheezing, coughing, and/or chest tightness.
- ▶ **Cobalt Naphthenate** can irritate the lungs. Repeated exposure may cause bronchitis to develop with coughing, phlegm, and/or shortness of breath.
- ▶ Repeated exposure may cause permanent lung scarring.

Medical

Medical Testing

Before beginning employment and at regular times after that, for frequent or potentially high exposures, the following is recommended:

- ▶ Chest x-ray (every 5 years) beginning 10 years after exposure

If symptoms develop or overexposure is suspected, the following are recommended:

- ▶ Evaluation by a qualified allergist can help diagnose skin allergy.
- ▶ Lung function tests. The results may be normal if the person is not having an attack at the time of the test.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- ▶ Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

In addition, the following may be useful or required:

- ▶ Use a vacuum or a wet method to reduce dust during clean-up. DO NOT DRY SWEEP.
- ▶ Use a high efficiency particulate air (HEPA) filter when vacuuming. Do not use a standard shop vacuum.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Cobalt Naphthenate**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ Safety equipment manufacturers recommend *Silver Shield®/4H®*, *Rubber* or *Nitrile* gloves for solid **Cobalt Naphthenate** and DuPont *Tyvek®*, or equivalent, is recommended as a protective material for clothing.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear eye protection with side shields or goggles.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- ▶ Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ Where the potential exists for overexposure to **Cobalt Naphthenate**, use a NIOSH approved full facepiece negative pressure, air purifying, particulate filter respirator. The filter classifications of dust/mist/fume, paint spray or pesticide prefilters, and filters for radon daughters, have been replaced with the N, R, and P series. Each series has three levels of filtering efficiency: 95%, 99%, and 99.9%.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Cobalt Naphthenate**, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.
- ▶ Consider all potential sources of exposure in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- ▶ Where the potential for high exposure exists, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ **Cobalt Naphthenate** is a COMBUSTIBLE SOLID.
- ▶ Use dry chemical, CO₂, water spray or foam as extinguishing agent.
- ▶ POISONOUS GASES ARE PRODUCED IN FIRE, including *Cobalt Oxide*.
- ▶ Use water spray to keep fire-exposed containers cool.
- ▶ FIRE MAY RESTART AFTER IT HAS BEEN EXTINGUISHED.
- ▶ **Cobalt Naphthenate** in *powder* or *granular* form may explode when mixed in air.

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Cobalt Naphthenate** is spilled or leaked, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Collect powdered material in the most convenient and safe manner and deposit in sealed containers.
- ▶ It may be necessary to contain and dispose of **Cobalt Naphthenate** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Cobalt Naphthenate** you should be trained on its proper handling and storage.

- ▶ **Cobalt Naphthenate** is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE) and STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC).
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from MOISTURE.
- ▶ Sources of ignition, such as smoking and open flames, are prohibited where **Cobalt Naphthenate** is used, handled, or stored in a manner that could create a potential fire or explosion hazard.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health
Right to Know
PO Box 368
Trenton, NJ 08625-0368
Phone: 609-984-2202
Fax: 609-984-7407
E-mail: rtk@doh.state.nj.us
Web address: <http://www.nj.gov/health/eoh/rtkweb>

***The Right to Know Hazardous Substance Fact Sheets
are not intended to be copied and sold
for commercial purposes.***

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGs) are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values are intended to provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database maintained by federal EPA. The database contains information on human health effects that may result from exposure to various chemicals in the environment.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

PIH is a DOT designation for chemicals which are Poison Inhalation Hazards.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Common Name: **COBALT NAPHTHENATE**

Synonyms: Cobalt Naphtha; Naftolite

CAS No: 61789-51-3

 Molecular Formula: $\text{Co}(\text{C}_{11}\text{H}_{10}\text{O}_2)_2$

RTK Substance No: 0523

 Description: Brown powder or bluish-red solid which is often used in a solution of *Mineral Oil* or *Mineral Spirits*

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
2- Health 2 - Fire 0 - Reactivity DOT#: UN 2001 ERG Guide #: 133 Hazard Class: 4.1 (Flammable solids)	Use dry chemical, CO ₂ , water spray or foam as extinguishing agent. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Cobalt Oxide</i> . Use water spray to keep fire-exposed containers cool. FIRE MAY RESTART AFTER IT HAS BEEN EXTINGUISHED. Cobalt Naphthenate in powder or granular form may explode when mixed in air.	Cobalt Naphthenate is not compatible with OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE) and STRONG ACIDS (such as HYDROCHLORIC, SULFURIC and NITRIC).

SPILL/LEAKS

Isolation Distance:

Spills: 25 meters (75 feet)

Fire: 800 meters (1/2 mile)

Collect powdered material in the most convenient and safe manner and deposit in sealed containers.

Aquatic life may be harmed by exposure to this chemical.

PHYSICAL PROPERTIES

Odor Threshold:	Odorless (solution may have Mineral Spirits odor)
Flash Point:	121°F (49°C)
LEL:	0.07%
UEL:	6%
Auto Ignition Temp:	529°F (276°C)
Vapor Density:	3.9 (air = 1)
Vapor Pressure:	1 mm Hg at 77°F (25°C)
Specific Gravity:	0.95 (water = 1)
Water Solubility:	Insoluble
Boiling Point:	515°F (268°C)
Molecular Weight:	407

EXPOSURE LIMITS

No occupational exposure limits have been established.

PROTECTIVE EQUIPMENT

Gloves:	Silver Shield®/4H®, Rubber or Nitrile for solid Cobalt Naphthenate
Coveralls:	DuPont Tyvek® for solid Cobalt Naphthenate
Respirator:	Full facepiece APR respirator with a High efficiency particulate filter or Supplied air

HEALTH EFFECTS

Eyes:	Irritation
Skin:	Irritation, skin allergy with itching and rash
Inhalation:	Nose, throat and lung irritation with coughing, wheezing and shortness of breath
Chronic:	Cobalt and Cobalt compounds may cause lung cancer in humans.

FIRST AID AND DECONTAMINATION

Remove the person from exposure.

Flush eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn.

Quickly remove contaminated clothing and wash contaminated skin with large amounts of soap and water.

Begin artificial respiration if breathing has stopped and CPR if necessary.

Transfer to a medical facility.