



Right to Know Hazardous Substance Fact Sheet

Common Name: **ETHYLENE DIBROMIDE**

Synonyms: EDB; Ethylene Bromide

Chemical Name: Ethane, 1,2-Dibromo-

Date: August 2001 Revision: December 2010

CAS Number: 106-93-4

RTK Substance Number: 0877

DOT Number: UN 1605

Description and Use

Ethylene Dibromide is a colorless, thick liquid with a slightly sweet, pleasant odor. It is used in waterproofing, as a solvent for plastics, resins and waxes, as a fumigant for tree crops, and in making dyes and pharmaceuticals.

Reasons for Citation

- ▶ **Ethylene Dibromide** is on the Right to Know Hazardous Substance List because it is cited by OSHA, ACGIH, DOT, NIOSH, NTP, DEP, IARC, IRIS, NFPA and EPA.
- ▶ This chemical is on the Special Health Hazard Substance List.

[SEE GLOSSARY ON PAGE 5.](#)

FIRST AID

Eye Contact

- ▶ Immediately flush with large amounts of water for at least 30 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while flushing. Seek medical attention.

Skin Contact

- ▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of soap and water. Seek medical attention.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.
- ▶ Medical observation is recommended for 24 to 48 hours after overexposure, as pulmonary edema may be delayed.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222

CHEMTREC: 1-800-424-9300

NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

EMERGENCY RESPONDERS >>>> SEE LAST PAGE

Hazard Summary

Hazard Rating	NJDOH	NFPA
HEALTH	-	3
FLAMMABILITY	-	0
REACTIVITY	-	0
CARCINOGEN POISONOUS GASES ARE PRODUCED IN FIRE DOES NOT BURN		

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious; 4=severe

- ▶ **Ethylene Dibromide** can affect you when inhaled and by passing through the skin.
- ▶ **Ethylene Dibromide** is a CARCINOGEN and MUTAGEN. HANDLE WITH EXTREME CAUTION.
- ▶ **Ethylene Dibromide** may cause reproductive damage.
- ▶ Contact can severely irritate and burn the skin and eyes with possible eye damage.
- ▶ Prolonged or repeated contact can cause skin dryness, redness and blisters.
- ▶ Inhaling **Ethylene Dibromide** can irritate the nose and throat.
- ▶ Inhaling **Ethylene Dibromide** can irritate the lungs. Higher exposures may cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency.
- ▶ High exposure can cause headache, nausea, vomiting, dizziness, drowsiness, unconsciousness and coma.
- ▶ **Ethylene Dibromide** may damage the liver and kidneys.

Workplace Exposure Limits

OSHA: The legal airborne permissible exposure limit (PEL) is **20 ppm** averaged over an 8-hour workshift, **30 ppm** not to be exceeded during any 15-minute work period, **and 50 ppm** as a maximum peak exposure not to be exceeded during any 5-minute work period.

NIOSH: The recommended airborne exposure limit (REL) is **0.045 ppm** averaged over a 10-hour workshift **and 0.13 ppm**, not to be exceeded during any 15-minute work period.

ACGIH: An exposure limit has not been determined for this suspected carcinogen.

- ▶ **Ethylene Dibromide** is a PROBABLE CARCINOGEN in humans. There may be no safe level of exposure to a carcinogen, so all contact should be reduced to the lowest possible level.
- ▶ The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ▶ For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ▶ You have a right to this information under the New Jersey Worker and Community Right to Know Act and the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Ethylene Dibromide**:

- ▶ Contact can severely irritate and burn the skin and eyes with possible eye damage.
- ▶ Inhaling **Ethylene Dibromide** can irritate the nose and throat.
- ▶ Inhaling **Ethylene Dibromide** can irritate the lungs causing coughing and/or shortness of breath. Higher exposures may cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency, with severe shortness of breath.
- ▶ High exposure can cause headache, nausea, vomiting, dizziness, drowsiness, unconsciousness and coma.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Ethylene Dibromide** and can last for months or years:

Cancer Hazard

- ▶ **Ethylene Dibromide** is a PROBABLE CARCINOGEN in humans. It has been shown to cause nasal cavity, circulatory system, mammary gland, and other types of cancer in animals.

- ▶ Many scientists believe there is no safe level of exposure to a carcinogen.

Reproductive Hazard

- ▶ **Ethylene Dibromide** may damage the testes (male reproductive glands) causing abnormal sperm and decrease fertility in females.

Other Effects

- ▶ Prolonged or repeated contact can cause a skin dryness, redness and blisters.
- ▶ **Ethylene Dibromide** may damage the liver and kidneys.
- ▶ **Ethylene Dibromide** can irritate the lungs. Repeated exposure may cause bronchitis to develop with coughing, phlegm, and/or shortness of breath.

Medical

Medical Testing

For frequent or potentially high exposure (half the REL or greater), the following are recommended before beginning work and at regular times after that:

- ▶ Liver and kidney function tests

If symptoms develop or overexposure is suspected, the following are recommended:

- ▶ Chest x-ray and lung function tests

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

- ▶ Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.
- ▶ More than light alcohol consumption can cause liver damage. Drinking alcohol may increase the liver damage caused by **Ethylene Dibromide**.

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- ▶ Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- ▶ Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- ▶ Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ▶ Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

In addition, the following may be useful or required:

- ▶ Where possible, transfer **Ethylene Dibromide** from drums or other containers to process containers in an enclosed system.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Ethylene Dibromide**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- ▶ The recommended glove materials for **Ethylene Dibromide** are Polyvinyl Alcohol, Silver Shield®/4H®, Viton and Barrier®.
- ▶ The recommended protective clothing materials for **Ethylene Dibromide** are Tychem® BR, TK and CSM, or the equivalent.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear indirect-vent, impact and splash resistant goggles when working with liquids.
- ▶ Wear a face shield along with goggles when working with corrosive, highly irritating or toxic substances.
- ▶ Do not wear contact lenses when working with this substance.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- ▶ Where the potential exists for exposure over **0.045 ppm**, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus or an emergency escape air cylinder.
- ▶ Exposure to **100 ppm** is immediately dangerous to life and health. If the possibility of exposure above **100 ppm** exists, use a NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode equipped with an emergency escape air cylinder.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- ▶ Extinguish fire using an agent suitable for type of surrounding fire. **Ethylene Dibromide** itself does not burn.
- ▶ **POISONOUS GASES ARE PRODUCED IN FIRE**, including *Hydrogen Bromide*.
- ▶ Use water spray to keep fire-exposed containers cool.

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Ethylene Dibromide** is spilled or leaked, take the following steps:

- ▶ Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- ▶ Absorb liquids in dry sand, earth, or a similar material and place into sealed containers for disposal.
- ▶ Ventilate area of spill or leak.
- ▶ Use foam to blanket release and suppress vapors.
- ▶ DO NOT wash into sewer.
- ▶ It may be necessary to contain and dispose of **Ethylene Dibromide** as a HAZARDOUS WASTE. Contact your state Department of Environmental Protection (DEP) or your regional office of the federal Environmental Protection Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Ethylene Dibromide** you should be trained on its proper handling and storage.

- ▶ A regulated, marked area should be established where **Ethylene Dibromide** is handled, used, or stored.
- ▶ **Ethylene Dibromide** may react violently with *powdered* ALUMINUM, MAGNESIUM and ZINC.
- ▶ **Ethylene Dibromide** may react with SODIUM; POTASSIUM; CALCIUM; LIQUID AMMONIA; OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); and STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE) to cause fires and explosions.
- ▶ **Ethylene Dibromide** decomposes on HOT SURFACES to form toxic and corrosive *Hydrogen Bromide* and *Bromine gases*.
- ▶ Store in tightly closed containers in a cool, well-ventilated area away from MOISTURE, LIGHT and HEAT.
- ▶ **Ethylene Dibromide** attacks RUBBER, some PLASTICS and COATINGS.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health
Right to Know
PO Box 368
Trenton, NJ 08625-0368
Phone: 609-984-2202
Fax: 609-984-7407
E-mail: rtk@doh.state.nj.us
Web address: <http://www.nj.gov/health/eoh/rtkweb>

***The Right to Know Hazardous Substance Fact Sheets
are not intended to be copied and sold
for commercial purposes.***

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGLs) are established by the EPA. They describe the risk to humans resulting from once-in-a-lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

The **critical temperature** is the temperature above which a gas cannot be liquefied, regardless of the pressure applied.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database on human health effects that may result from exposure to various chemicals, maintained by federal EPA.

LEL or Lower Explosive Limit, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

Protective Action Criteria (PAC) are values established by the Department of Energy and are based on AEGLs and ERPGs. They are used for emergency planning of chemical release events.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or Upper Explosive Limit is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Air*), at the same temperature and pressure.

The **vapor pressure** is a force exerted by the vapor in equilibrium with the solid or liquid phase of the same substance. The higher the vapor pressure the higher concentration of the substance in air.

Common Name: **ETHYLENE DIBROMIDE**

Synonyms: EDB; Ethylene Bromide

CAS No: 106-93-4

 Molecular Formula: C₂H₄Br₂

RTK Substance No: 0877

Description: Colorless, thick liquid with a slightly sweet, pleasant odor

HAZARD DATA

Hazard Rating	Firefighting	Reactivity
3 - Health 0 - Fire 0 - Reactivity DOT#: UN 1605 ERG Guide #: 154 Hazard Class: 6.1 (Poison)	Extinguish fire using an agent suitable for type of surrounding fire. Ethylene Dibromide itself does not burn. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Hydrogen Bromide</i> . Use water spray to keep fire-exposed containers cool.	Ethylene Dibromide may react violently with <i>powdered</i> ALUMINUM, MAGNESIUM and ZINC. Ethylene Dibromide may react with SODIUM; POTASSIUM; CALCIUM; LIQUID AMMONIA; OXIDIZING AGENTS (such as PERCHLORATES, PEROXIDES, PERMANGANATES, CHLORATES, NITRATES, CHLORINE, BROMINE and FLUORINE); and STRONG BASES (such as SODIUM HYDROXIDE and POTASSIUM HYDROXIDE) to cause fires and explosions. Ethylene Dibromide decomposes on HOT SURFACES to form toxic and corrosive <i>Hydrogen Bromide</i> and <i>Bromine</i> gases.

SPILL/LEAKS

Isolation Distance:

Spill: 30 meters (100 feet)

Fire: 800 meters (1/2 mile)

Absorb liquids in dry sand, earth, or a similar material and place into sealed containers for disposal.

Use foam to blanket release and suppress vapors.

Ethylene Dibromide may be hazardous to the environment.

PHYSICAL PROPERTIES

Odor Threshold:	Slightly sweet
Flash Point:	Noncombustible
Vapor Density:	6.5 (air = 1)
Vapor Pressure:	12 mm Hg at 68°F (20°C)
Specific Gravity:	2.2 (water = 1)
Water Solubility:	Very slightly soluble
Boiling Point:	268° to 270°F (131° to 132°C)
Melting Point:	50°F (10°C)
Ionization Potential:	9.45 eV
Molecular Weight:	187.8

EXPOSURE LIMITS

OSHA: 20 ppm, 8-hr TWA; 30 ppm, Ceiling; 50 ppm Peak (5 min.)

NIOSH: 0.045, 10-hr TWA; 0.13 ppm, Ceiling

IDLH: 100 ppm

The Protective Action Criteria values are:

PAC-1 = 17 ppm PAC-2 = 24 ppm PAC-3 = 46 ppm

PROTECTIVE EQUIPMENT

Gloves:	Polyvinyl Alcohol, Silver Shield®/4H®, Viton and Barrier® (>8-hr breakthrough)
Coveralls:	Tychem® BR, TK and CSM (>8-hr breakthrough)
Respirator:	SCBA

HEALTH EFFECTS

Eyes:	Irritation and burns
Skin:	Irritation and burns
Inhalation:	Nose, throat and lung irritation with coughing, and severe shortness of breath (pulmonary edema) Headache, dizziness, drowsiness, unconsciousness and coma
Chronic:	Cancer (nasal cavity, circulatory system, mammary gland, and other sites) in animals

FIRST AID AND DECONTAMINATION

Remove	the person from exposure.
Flush	eyes with large amounts of water for at least 30 minutes. Remove contact lenses if worn. Seek medical attention.
Quickly	remove contaminated clothing and wash contaminated skin with large amounts of soap and water. Seek medical attention.
Begin	artificial respiration if breathing has stopped and CPR if necessary.
Transfer	promptly to a medical facility.
Medical	observation is recommended as symptoms may be delayed.