



FACTS ABOUT RESPIRATORY PROTECTION FOR PUBLIC EMPLOYEES



Public Employees
Occupational Safety and
Health Program

Heather Howard, J.D.
Commissioner

Jon S. Corzine
Governor

David J. Socolow
Commissioner

Revised
March, 2007

- **What Is a Respirator?**
- **Why Do Employees Need Respirators?**
- **When Do Employees Need to Wear Respirators?**
- **What Procedures Are Necessary to Ensure Proper Protection?**
- **How Do You Develop An Effective Respirator Program?**
- **How Do You Choose the Correct Respirator?**
- **Who Needs to Be Trained?**
- **Do You Need to Do Medical Evaluations?**
- **How Do You Make Sure the Respirators Fit Properly?**
- **How Do You Inspect and Take Care of Respirators?**
- **How Do You Monitor Work Areas?**
- **What Equipment and Air Quality Standards Apply?**
- **What Other Help Can the PEOSH Program Provide?**
- **What Are Some Specific Respirator Uses?**



What Is a Respirator?

A respirator is an enclosure that covers the nose and mouth or the entire face or head. Respirators can have two general types of fit: (1) tight-fitting—that is a filtering face piece, quarter masks, which cover the mouth and nose; half masks, which cover the face from the hairline to below the chin; and full face masks which cover the entire face; and (2) loose-fitting, such as hoods, helmets, blouses, or full suits that cover the head completely.



There are two major classes of respirators: (1) air-purifying to remove contaminants from the air, and (2) atmosphere-supplying to provide clean, breathable air from an uncontaminated source. As a general rule, the latter-type respirator is used for more hazardous exposures.

Why Do Employees Need Respirators?

Some of the most common hazards to employees' lungs are the lack of oxygen and the presence of harmful dusts, fogs, smokes, mists, fumes, gases, vapors, or sprays including substances that may cause adverse neurological effects, lung impairment and cancer.

There are many workplace situations that involve toxic substances and for which engineering controls may be inadequate to control exposures. In these situations respirators are used as a back-up method of protection. Respirators can also protect against oxygen-deficient atmospheres. Increased breathing

rates, accelerated heartbeat, and impaired thinking or coordination occur more quickly in an oxygen-deficient atmosphere. Even a momentary loss of coordination may be devastating to a worker if it occurs while the worker is performing a potentially dangerous activity, such as climbing a ladder.

When Do Employees Need to Wear Respirators?

Respirators must be used when hazards are present and effective engineering controls are not feasible, or engineering controls are being installed or during emergency situations.

The prevention of atmospheric contamination at the worksite generally should be accomplished if feasible, by engineering control measures—such as enclosing or confining the contaminant-producing operation, local exhaustion of the contaminant—or substituting with less toxic materials.

Respirators have their limitations and are not a substitute for effective engineering controls. Where respirators are required to protect worker health, specific procedures are necessary to ensure the effectiveness of the equipment.

What Procedures Are Necessary to Ensure Proper Protection?

The Public Employees Occupational Safety and Health (PEOSH) Program's Respiratory Protection Standard (29 CFR 1910.134) requires that employers establish and maintain an effective respiratory protection program—different hazards require different respirators—and employees are responsible for wearing the respirator and complying with the program.

The standard contains requirements for program administration, worksite-specific procedures, respirator selection, employee training, fit testing, medical evaluation, and respirator use, cleaning, storage, maintenance, and repair.

The respirators issued to the employee must be properly selected, used, and maintained for a particular work environment and contaminant, and employees must be trained in all aspects of the respiratory protection program.

How Do You Develop An Effective Respirator Program?

When planning a program to control occupational illness caused by breathing air contaminated with harmful dusts, fogs, fumes, mists, gases, smokes, vapors, or sprays, the primary objective should be prevention.

Responsibility for the program must rest with one person. The **program administrator** must have sufficient knowledge of the subject to supervise the program properly. Larger public employers with industrial hygiene, medical, safety engineering, or fire prevention departments should administer the program in liaison with the program administrator. For smaller employers the program should be administered by a qualified person, such as an upper-level superintendent or foreman.

A respirator program should stress thorough training of all users. Employees must be aware that the respirators do not eliminate the hazards. If the respirator fails, overexposure may occur. To reduce the possibility of failure, respirators must fit properly and be maintained in a clean and serviceable condition. Employers and employees must understand the respirator's purpose and its limitations. The respirator must not be altered or removed by the wearer even for a short time, despite the fact the wearer may find it uncomfortable.

An effective respirator program must cover the following factors:

- written worksite specific procedures;
- program evaluation;
- selection of approved respirators;
- training;
- fit testing;
- inspection, cleaning, maintenance and storage;
- medical evaluations;
- work area surveillance.

When respirator use is required, employers must have written operating procedures for the safe and proper use of respirators. Users must be familiar with these procedures as well as with available respirators, and their limitations. In workplaces with no hazardous exposures, but where there is voluntary respirator use, certain written program elements may be necessary to prevent potential hazards associated with respirator use.

The effectiveness of a respirator program must be evaluated regularly and the written operating procedure modified as necessary to reflect the evaluation results. The use of a labor-management team may be effective for the periodic evaluation.

How Do You Choose the Correct Respirator?

Choosing the right equipment involves determining what the hazard is, choosing approved equipment, and ensuring that the device is certified by the National Institute for Occupational Safety and Health (NIOSH). Equipment must be used pursuant to the conditions accompanying the certification.

Chemical and physical properties of the contaminant, as well as the toxicity and concentration of the hazardous material and the amount of oxygen present, must be considered in selecting the proper respirators. The nature and extent of the hazard, work rate, area to be covered, mobility, work requirements and conditions, as well as the limitations and characteristics of the available respirators also are selection factors.

Air-purifying respirators use filters or sorbents to remove harmful substances from the air. They range from simple disposable masks to sophisticated devices.



Air-purifying respirators do not supply oxygen and may not be used in oxygen-deficient atmospheres or in ones that are immediately dangerous to life or health (IDLH).

Atmosphere-supplying respirators are designed to provide breathable air from a clean air source other than the surrounding contaminated work atmosphere. They range from supplied-air respirators and self-contained breathing apparatus (SCBA) to complete air-supplied suits.

Time

- The time needed to perform a given task, including the time necessary to enter and leave a contaminated area, is one factor that determines the type of respiratory protection needed. For example, SCBAs, gas-masks, or air-purifying chemical-cartridge respirators provide respiratory protection for relatively short periods whereas a type of atmosphere-supplying respirator that supplies breathable air from an air compressor through an airline can provide protection for extended periods of time. Particulate filter air-purifying respirators can provide protection for long periods without the need of filter replacement **only** if the total concentration of atmospheric particulates is low. Where there are higher concentrations of contaminants, however, an atmosphere-supplying respirator such as the positive-pressure supplied-air respirator (SAR) offers the advantage of better protection and longer duration.

The use of SARs also avoids the need to be concerned about determining filter breakthrough times, change schedules, or using end-of-service-life indicators (ESLI) for airborne toxic materials, a factor that must be considered when using air-purifying respirators. SARs also cause less discomfort than air-purifying respirators because the wearer need not overcome filter resistance when inhaling.

Interference with Movement

- Air-purifying respirators present minimal interference with the wearer's movement. Atmosphere-supplying respirators, however, may restrict movement and present potential hazards. For example, SARs with their trailing hoses, can limit the area the wearer can cover and may present

a potential hazard where the trailing hose can come into contact with machinery. Similarly, SCBAs include a back-mounted compressed-air cylinder which presents both a size and weight burden. This may restrict climbing and movement in tight places, and carrying the added weight of the air cylinder presents an additional stress.

Breathing Volume

- Another factor to consider when using respirators is the air-supply rates. The wearer's work rate determines the volume of air breathed per minute. The volume of air supplied to meet the breathing requirements is of great significance when using atmosphere-supplying respirators such as self-contained and air-line respirators that use cylinders because this volume determines their operating life. The useful service life of these respirators under even moderate working conditions may be significantly less than under conditions of rest.

The peak airflow rate also is important in the use of a constant-flow SAR. The air-supply rate should always be greater than the maximum amount of air being inhaled in order to maintain the respiratory enclosure under positive pressure.

Higher breathing resistance of air-purifying respirators under conditions of heavy work may result in distressed breathing. A person working in an area of high temperature or humidity is also under stress. Additional stress resulting from the use of a respirator should be minimized by using one having a minimal weight and a minimal breathing resistance when these can be fitted properly to the wearer.

Warning of Remaining Service Life

- Some type of warning as to the remaining service life is available for SCBAs and for some chemical canister respirators. This may be a pressure gauge or timer with an audible alarm for SCBAs or a color-end-of-service-life indicator (ESLI) on the cartridge or canister. The user should understand the operation and limitations of each type of warning device. Since many gas masks and chemical-cartridge

respirators have no ESLI for their remaining service life, the employer or employee will need to do service life calculations. It is important, therefore, that new canisters and cartridges be used at the beginning of each work shift.

Who Needs to Be Trained?

Supervisors and workers must be trained regarding the proper selection, use, and maintenance of respirators.

All employees required to use respiratory protective equipment must be instructed in the proper use of the equipment and its limitations. Those employees who will be required to use respiratory protective equipment in atmospheres immediately dangerous to life or health must be trained in rescue procedures.

Training must be comprehensive enough so that, when completed, the employee will be able to demonstrate a knowledge of the limitations and capabilities of the respirator, why the respirator is necessary, and how improper fit, usage, or maintenance can compromise the respirator.

Training must include an explanation of the following:

- Nature of the respiratory hazard and what may happen if the respirator is not used properly,
- Engineering and administrative controls being used and the need for the respirator as added protection,
- Reason(s) for the selection of a particular type of respirator,
- Limitations of the selected respirator,
- Methods of donning the respirator, performing a user seal check, and ensuring proper operation,
- Proper wear of the respirator,
- Respirator maintenance and storage, and
- Proper method for handling emergency situations.

Users should know that improper respirator use or maintenance may cause overexposure. They should know that continued use of poorly fitted and maintained respirators can also cause chronic disease or death from overexposure to air contaminants.

Do You Need to Do Medical Evaluations?

Persons assigned to tasks that require the use of a respirator must be physically able to perform their work while using the respirator. The local physician or licensed health care professional must determine what health and physical conditions are pertinent. An employee's ability to use a respirator is determined using a medical questionnaire or an initial medical examination that provides the same information. **The employer must provide additional medical evaluations under the following four conditions:**

1. When an employee reports medical signs or symptoms that are related to the ability to use a respirator.
2. The employer is informed by the physician or other licensed health care professional that the employee needs to be re-evaluated.
3. If during fit testing or respiratory program evaluation, a need for employee re-evaluation is found.
4. If there is a change in workplace conditions that may place additional physiological burden on the worker.

Follow-up medical evaluations may include any medical tests, consultations, or diagnostic procedures that the physician or licensed health care professional determines necessary to render a decision as to the ability of the employee to wear or continue to wear a respirator. A written recommendation as to the ability of the employee is provided to the employer by the physician or the licensed health care professional.

How Do You Make Sure the Respirators Fit Properly?

Full facepieces, half masks, quarter masks and even the different brands of the same type of respirator marketed, have different fit characteristics. **No one respirator will fit everyone.** Employers need to have sufficient sizes and models available to achieve proper fit.

Corrective eyeglasses worn by employees also present a problem when fitting respirators. Special mountings are available to hold corrective lenses inside full facepieces. If corrective lenses are needed, the facepiece and lenses must be fitted by a qualified individual to provide good vision, comfort, and proper sealing. Contact lenses can be worn with any type respirator, however, it is not recommended when wearing a half-mask respirator in dusty atmospheres. The user must receive fitting instructions including demonstrations and practice in how to wear the respirator, how to adjust it, and how to determine if it fits properly.

Although respirators are designed for maximum efficiency, they cannot provide protection without a tight seal between the facepiece and the face of the wearer. Consequently, beards and other facial hair can substantially reduce the effectiveness of a respirator by breaking the seal. The absence of dentures can seriously affect the fit of a facepiece. To ensure proper respirator fit, a facepiece must be checked each time the respirator is worn. This can be accomplished by performing a positive-pressure or negative-pressure user seal check. Detailed instructions for performing these tests can be found in Appendix B-1 of the Respiratory Protection Standard (29 CFR 1910.134). The user seal check does not take the place of a fit test.

The effectiveness of the fit of the facepiece can be tested two ways: qualitatively and quantitatively.

Qualitative fit testing involves the introduction of a harmless odoriferous, or irritating substance into the breathing zone around the respirator being worn. If no odor or irritation is detected by the wearer, a proper fit is indicated.

Quantitative fit testing offers more accurate, detailed information on respirator fit. One method involves introducing a harmless aerosol to the wearer while in a test chamber. A second method uses controlled negative-pressure measurements to determine respirator fit. The tests require the wearer to perform exercises that could induce facepiece leakage, while the air inside and outside the facepiece is measured for the presence of an aerosol or ambient particulates,

or a pressure change, to determine any leakage into the respirator. The PEOSH accepted fit test methods are described in Appendix A of the Respiratory Protection Standard.

How Do You Inspect and Take Care of Respirators?

All respirators must be inspected for wear and deterioration of their components before and after each use. Special attention should be given to rubber or plastic parts that can deteriorate. The face-piece, especially the face seal surface, headband, valves, connecting tube, fittings, and canister must be in good condition. A respirator inspection must include a check of the tightness of the connections.



SCBAs used for emergencies only must be inspected at least monthly. Air and oxygen cylinders must be fully charged according to the manufacturer's instructions. Regulator and warning devices must be checked to ensure their proper function. Records must be kept of inspection dates and findings.

Chemical cartridges and gas mask canisters must be replaced as necessary to provide complete protection. The manufacturer's recommendations must be followed. Mechanical filters must be replaced as necessary to avoid high resistance to breathing.

Repairs must be made only by experienced persons using parts specifically designed for the respirator. The manufacturer's instructions should be consulted for any repair, and no attempt should be made to repair or replace components or make adjustments or repairs beyond the manufacturer's recommendations.

A respirator that has been used must be cleaned and disinfected before it is reissued. Emergency-use rescue equipment must be cleaned and disinfected immediately after each use.

Elastomeric respirators may be washed in a detergent solution and then disinfected by immersion in a sanitizing solution. Cleaner-sanitizers that effectively clean the respirator and contain a bactericidal agent are commercially available. The bactericidal agent frequently used is a quaternary ammonium compound. Strong cleaning and sanitizing agents and many solvents can damage rubber or elastomeric respirators parts. Such materials must be used with caution or after consultation with the respirator manufacturer. Refer to Appendix B-2 of the Respiratory Protection Standard for additional information.

Respirators must be stored to protect against dust, sunlight, heat, extreme cold, excessive moisture, or damaging chemicals. Protection against any mechanical damage should also be provided. Respirators should be stored so that facepieces and exhalation valves will rest in a normal position to prevent the rubber or plastic from reforming into abnormal shape.

How Do You Monitor Work Areas?

Surveillance of the conditions in the work area and of the degree of worker exposure or stress (combination of work rate, environmental conditions, and physiological burdens of wearing a respirator) must be maintained. Changes in operating procedures, temperature, air movement, humidity, and work practices may influence the concentration of a substance in the work area atmosphere. These factors necessitate periodic monitoring of the air contaminant concentration. In instances where work is of such short duration that time to carry out the testing exceeds the time of the job, reasonable estimates of exposure are allowable.

In situations where the environment is or may be immediately dangerous to life or health (IDLH), employers shall ensure that one employee or, when needed, more than one employee is located outside the dangerous environment and that visual, voice, or signal line communication is maintained between the employees in the IDLH atmosphere and employee(s)

outside. In interior structural firefighting situations employers must ensure that at least two employees enter the structure and remain in visual or voice contact with one another at all times. Also, at least two employees shall be located outside to provide effective emergency rescue.

What Equipment and Air Quality Standards Apply?

Compressed air, compressed oxygen, liquid air, and liquid oxygen used for respiration must be of high purity. Oxygen must meet the requirements of the United States Pharmacopoeia for medical or breathable oxygen. Breathable air must meet at least the requirement for Grade D breathable air described in Compressed Gas Association (CGA) *Commodity Specification G-7.1-1989*. Compressed oxygen must not be used in open circuit SCBAs or SARs that have previously used compressed air. Oxygen must never be used with air-line respirators.

Breathable air may be supplied to respirators from cylinders or air compressors. For testing cylinders, see *Shipping Container Specifications of the Department of Transportation (49 CFR Part 173 and Part 178)*.

Containers of breathable gas must be clearly marked (see *National Institute for Occupational Safety and Health, 42 CFR Part 84 requirements*). Further details on the sources of compressed air and its safe use can be found in the CGA pamphlet G-7.1-1989, mentioned above.

The compressor for supplying air must be equipped with the necessary safety devices and alarms. Compressors must be constructed and situated to avoid any entry of contaminated air into the system and must be equipped with suitable in-line, air-purifying sorbent beds and filters installed to ensure air quality. If an oil-lubricated compressor is used, it must have a high-temperature or carbon monoxide alarm or both. If only the high-temperature alarm is used, the air compressor must be tested frequently for carbon monoxide.

Air-line couplings must be incompatible with outlets for other gas systems to prevent accidental servicing of air-line respirators with nonrespirable gases or oxygen.

What Other Help Can the PEOSH Program Provide?

The PEOSH Program has a variety of products and programs available to help employers comply with its regulations and improve workplace safety and health. These include numerous publications on regulatory topics, such as asbestos and bloodborne pathogens.

Occupational Safety and Health Program Guidelines

Effective management of worker safety and health protection is a decisive factor in reducing the extent and severity of work-related injuries and illnesses and their related costs. To assist employers and employees in developing effective safety and health programs, the PEOSH program published *PEOSH Guidelines for Occupational Safety and Health Programs*. These guidelines apply to all places of employment covered by PEOSH.

The guidelines identify four general elements that are critical to the development of a successful safety and health program:

- Management commitment and employee involvement,
- Worksite analysis,
- Hazard prevention and control, and
- Safety and health training.

The guidelines recommend specific actions, under each of these general elements to achieve an effective safety and health program.

Consultation Services

The PEOSH Program offers occupational safety and health consultations to assess safety and health management systems and to identify hazards in order to help employers prevent accidents, injuries, illnesses and fatalities. The Consultation Program can also assist employers with the development of their respiratory protection program. This service is free to public employers and must be requested by managers or administrators. Free on-site safety and health training is available as well.

Electronic Information

Internet - PEOSH standards, educational material, brochures, and request for consultation and training forms can be found on the PEOSH web site at: <http://www.nj.gov.us/health/eoh/peoshweb>, or by calling the PEOSH Program at (609) 984-1863.

What Are Some Specific Respirator Uses?

The following list presents a simplified version of characteristics and factors used for respirator selection. It does not specify the contaminant concentrations or particle size. Some PEOSH substance-specific standards include more detailed information on respirator selection.

Hazard	Respirator (NIOSH Approval Required)
Oxygen Deficiency Immediately dangerous to life or health.*	Positive-pressure SCBA. Combination positive-pressure with auxiliary self-contained air supply.
Gas and vapor contaminants Immediately dangerous to life or health.	Positive-pressure SCBA. Combination positive-pressure SAR with auxiliary self-contained air supply respirator.
Not immediately dangerous to life or health.	Positive-pressure SAR. Gas mask. Chemical cartridge respirator.
Particulate contaminants	Positive-pressure SAR including abrasive blasting respirator. Powered air-purifying respirator equipped with high-efficiency filters. Air-purifying respirator with a specific particulate filter.
Gaseous and particulate contaminants Immediately dangerous to life or health.	Positive-pressure SCBA. Combination positive-pressure SAR with auxiliary self-contained air supply.
Not immediately dangerous to life or health.	Positive-pressure supplied-air respirator. Gas mask. Chemical-cartridge respirator.
Escape from contaminated atmosphere that may be immediately dangerous to life or health	Positive-pressure SCBA. Gas mask. Combination positive-pressure SAR with escape SCBA.
Firefighting	Positive-pressure SCBA.

***Note:** “Immediately dangerous to life or health” (IDLH) is any condition that poses either an immediate threat of severe exposure to contaminants, such as radioactive materials, which are likely to have adverse, delayed effects on health, would cause irreversible adverse health effects; or would impair a person’s ability to escape a dangerous environment.

For More Information

For employee complaint's, or to request an on-site consultation or more occupational health and safety information, contact the PEOSH Program at (609) 984-1863. The Facts About Respiratory Protection for Public Employees bulletin can be obtained from the PEOSH website at www.nj.gov/health/eoh/peoshweb.

This bulletin provides general information about respiratory protection and the development of a respiratory protection program. Consult the Respiratory Protection Standard, 29 CFR 1910.134, for more complete information about the requirements of the standard.

Document prepared by:
New Jersey Department of Health and Senior Services
Public Health Services Branch
Division of Epidemiology, Environmental, and Occupational Health
Occupational Health Service
Public Employees Occupational Safety and Health Program

**PEOSH PROGRAM
READER RESPONSE CARD**

Facts about Respiratory Protection for Public Employees

Dear Reader:

Please take a few minutes to help us evaluate this publication. Please check the following:

Check the category that best describes your position:

- | | | |
|--|---|--|
| <input type="checkbox"/> manager | <input type="checkbox"/> employee | <input type="checkbox"/> educator |
| <input type="checkbox"/> safety professional | <input type="checkbox"/> occupational health professional | <input type="checkbox"/> other (specify) |
| <input type="checkbox"/> researcher | <input type="checkbox"/> health care worker | _____ |
| | | _____ |

Check the category that best describes your workplace:

- | | | |
|--|--|---|
| <input type="checkbox"/> academia | <input type="checkbox"/> municipal government | <input type="checkbox"/> labor organization |
| <input type="checkbox"/> state government | <input type="checkbox"/> municipal utilities authority | <input type="checkbox"/> other (specify) |
| <input type="checkbox"/> county government | | _____ |
| | | _____ |

Describe how thoroughly you read this publication:

- | | |
|--|-------|
| <input type="checkbox"/> cover-to-cover | |
| <input type="checkbox"/> sections of interest only (specify) | _____ |
| <input type="checkbox"/> other (specify) | _____ |

How will you use this information (check all that apply):

- | | | |
|--|--|--|
| <input type="checkbox"/> change the work environment | <input type="checkbox"/> provide information | <input type="checkbox"/> not used |
| <input type="checkbox"/> change a procedure | <input type="checkbox"/> copy and distribute | <input type="checkbox"/> other (specify) |
| <input type="checkbox"/> assist in research | <input type="checkbox"/> in training | _____ |
| <input type="checkbox"/> change training curriculum | | _____ |

Which section did you find most useful?

Which section did you find the least useful and why?

Other occupational health information bulletins you would like to see the PEOSH Program develop.


Other comments and suggestions:

Cut here, fold in thirds, tape.





NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES



BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 206 TRENTON, NJ

POSTAGE WILL BE PAID BY ADDRESSEE

STATE OF NEW JERSEY
DEPT OF HEALTH & SENIOR SERVICES
PEOSH PROGRAM
PO BOX 360
TRENTON, NEW JERSEY 08625-9985

